

October 26, 1929

A McGraw-Hill Publication

20 Cents per Copy


AVIATION

The Oldest American Aeronautical Magazine

Great Britain's AIR ROUTE *Radio*
THE *British Government Airship*
THE GENERAL *Mailplane*



UNION CRANKSHAFTS for AIRCRAFT ENGINES




Two types of Union Crankshafts used in various aircraft engines

THIS organization is engaged in the manufacture of crankshafts for the nation's leaders in the aircraft industry. The superior qualities of Union Crankshafts are found in their fine finish together with utmost precision in every detail.



As the world's most noted producer of fine finished steel, backed by many years of experience in the making of crankshafts for both the auto and aero industries, you will find here those extensive modern facilities essential to meet your exacting requirements.

UNION DRAWN STEEL COMPANY
BEAVER FALLS, PA.



**A PERFECT POWER CURVE,
ALMOST A STRAIGHT LINE
OF POWER DEVELOPMENT**
THE TYPE B
AXELSON AIRPLANE ENGINE

Corner Randolph Street
and Doyle Avenue


Axelson Aircraft Engine Co.
Factory and General Office

Los Angeles, California
(P. O. Box 337)

THE "REASON-WHY" OF RYAN PERFORMANCE



RYAN'S outstanding performance is not a matter of chance. Every detail of design and construction contributes to brilliance in the air. From the installation of the 300 H.P. radial engine—in perfect relationship to the airplane's design—to the streamlining of struts, Ryan engineering has had as its primary object the achieving of speed and reliability with economy of operation.



350 FEET, 10 TO 12 SECONDS

QUICK TAKE-OFF. Ryan gets off the ground quickly because of abundant power and low weight. Fully loaded they take off in 350 feet—and in 10 to 12 seconds' time.



1000 FEET, PER MINUTE

RAPID CLIMB. The slant of Ryan airplanes to climb 1200 feet per minute results from low weight per horsepower, high-lift wing sections and careful streamlining.

STABILITY in the air is the result of Ryan's ample control area and the balance achieved by the proper grouping of the center line of thrust, the center line of resistance, the center of gravity and the center of lift.



10000 FEET

HIGH CEILING. Ryan's 18,000-foot service ceiling is possible because of low horsepower loading, high lift wing sections of low drag and thoroughly streamlined design.



500 TO 300 FEET

SLOW LANDING. Slow landing is achieved through large wing area and resultant low wing loading, together with low weight. Ryan can be set down in 300 to 350 feet.

LONG LIFE is obtained by building Ryan airplanes with more-than-necessary ruggedness and larger factors of safety in all working parts than Department of Commerce specifies. Write for catalog containing complete information.

The Ryan will be displayed at the Western Aircraft Show, Los Angeles, November 6th—10th.

RYAN AIRCRAFT CORPORATION
Lansdale—St. Louis Airport, Eadsburg, Mo.
division of
DETROIT AIRCRAFT CORPORATION
EXECUTIVE OFFICE: Union Trust Building, Detroit

BUILDERS OF LINDBERGH'S "SPIRIT OF ST. LOUIS"

Department of Commerce Approval Type Certificate No. 404, including land gear and power



SCINTILLA AIRCRAFT MAGNETOS

serve the
BOEING
TRANSCONTINENTAL
TRANSPORTS



During 18 Passenger
Transcontinental Transport

Giant Boeing Transcontinental Eighteen Passenger Tri-Motored Transports are powered with Pratt & Whitney "Hornet" engines equipped with SCINTILLA AIRCRAFT MAGNETOS and IGNITION SWITCHES.

The dependable performance of SCINTILLA AIRCRAFT MAGNETOS helps to make possible daily transport schedules.

The majority of modern American Aeronautical Engines are equipped with Scintilla Aircraft Magneto.



The type of Scintilla Aircraft Magneto with which the "Hornet" engines are equipped.

They are selected because of their—

Dependability—Simplicity
Accessibility



Pratt & Whitney
"Hornet"

SCINTILLA MAGNETO CO. Inc.
SIDNEY — NEW YORK
Contributors to the U.S. Army and Navy

Known in Europe as the Schreck . . . F B A

The Viking Amphibian and Flying Boat is the American interpretation of the European F B A built by Mr. Louis Schreck who for fifteen years has concentrated upon the development of a most unique size flying boat.

The Schreck is known in Europe, Asia, South America and Canada . . . behind it is a record of 6,000,000 miles without a structural accident. It is standard equipment in the French Navy.

Founded upon Schreck experience . . . built in America, by American workmen . . . powered with an American engine the Viking is a plane of sturdy construction, exceptional stability, safe flying qualities, and fine all-around performance. We shall be glad to send you full particulars.

THE VIKING FLYING BOAT COMPANY

89 Sheldon Avenue, New Haven, Conn.

R. E. GROSS, President R. E. THOMAS, Vice-President and Gen. Mgr.

Specifications of the Viking—Vo 2

Span	48' 3"	Power Loading	15.0 lbs. per H. P.
Length	52' 6"	High Speed	100 mph
Height (on wheels)	17' 2"	Cruise Speed	80 mph
Wing Area	661 sq. ft.	Landing Speed	40 mph
Weight Empty	7500 lbs.	Climb (on land) 5000 ft. per min.	
Useful Load	1000 lbs.	Service Ceiling	14,000 ft.
Per Hour	500 lbs.	Ref. Capacity	50 gal.
Endured Weight	5500 lbs.	Range	200 miles
Wing Loading 7500 lbs. per sq. ft.		Durability	4 1/2 hours
Engine—Wright J-6, 300—325 H. P. (Photo shows Hispano-Suiza)			

THE VIKING FLYING BOAT



SHERWIN-WILLIAMS asks a question—

"Just how incidental is finish?"

Perhaps you've heard that, in the case of airplanes, finish is purely incidental, that the fact doesn't matter so long as it looks well. The fact is that if the finish does not protect sufficiently you are faced with the rotting and disintegration of fabric by the direct attack of weather. And this means the unnecessary maintenance and expense of a new fabric application.

Sherwin-Williams Aero Finishes protect

A finish that is "bulletproof," as it is the case with glossy types, really "covers" it. And it is so little it cracks when in as little time as six months.

The new, perfected S-W Aero Finisher soak into the fabric, are a part of it and sport from it. Endorsing a "soak-in," they are flexible and inherently elastic to stand engine vibration without cracking. They too, the use of opaque opaque pigmented dopes keeps the sun from reaching the fabric. And all S-W Aero

Finishes have smooth, lustrous surfaces. They mean the maximum of fabric strength.

Write for new finishing handbook

Sherwin-Williams Finishing Handbooks, recently prepared by Sherwin-Williams, gives complete flight finish information on the finishing problem. It tells all about the new S-W line of Chloro-Dispers, Semi-Dispersed Dopes, Gloss Aero Finishes and all other finishes specially prepared for every wood, metal and fabric surface made and painted. It also suggests various methods, refinish, color combinations and contrasts.

In years of experience produce real flying finish.

The Sherwin-Williams Co.
Cleveland, Ohio



THE SHERWIN-WILLIAMS CO., CHRY. 781
100 East Bank St. Cleveland, Ohio
Please send me complete details on Sherwin-Williams Aero Finishes.


Name _____
Address _____
City _____

SHERWIN-WILLIAMS AERO FINISHES

For Planes, Banners and Equipment

DROP FORGINGS FOR RELIABILITY

The forgings below were made on Chambersburg hammers and represent parts used in many of the most famous flights in recent years.



MUCH of the success of distance flights depends on the capacity of light steel parts to resist fatigue. The standardization and increased reliability of airplanes today, as compared with those that fought the war, is due to a considerable extent to the improvement in steel quality.

Naturally, therefore, forgings enter more and more into airplane construction. They have a higher factor of safety and greater strength in proportion to their bulk than parts made by any other process. Drop forged parts have contributed materially to the success of the great endurance and distance flights of recent times.

The speed, accuracy and capacity for continuous operation of Chambersburg Hammers have earned them the favor of important manufacturers of airplane parts.

CHAMBERSBURG ENGINEERING COMPANY

CHAMBERSBURG, PENNA.

Solely by

CHAMBERSBURG-NATIONAL

COMPLETE FORGING EQUIPMENT

CHAMBERSBURG, PA. TAYLOR, OHIO
New York, 322 W. 43rd St. Chicago, 331 W. Washington St.
Detroit, 2427 Woodward Avenue

CHAMBERSBURG HAMMERS



MODEL 40-BOARD DROP HAMMER



"Wasp" and "Hornet" service nation wide

FROM coast to coast . . . Canada in the Canal Zone . . . in strategic centers of the nation . . . The Pratt & Whitney Aircraft Company has established twenty-four authorized service and parts stations to further insure the internationally famous dependability of "WASP" and "HORNET" engines.

Big service . . . unique in the annals of aircraft history . . . without the superior equipment and experienced personnel of the large air transport operators, 90 per cent of whom use "WASP" or "HORNET" equipment. It is backed by the Pratt & Whitney Aircraft Company and is under the supervision of men well trained in the company's plant. These transport operators have facilities equal to factory facilities and a personnel whose experience has been built up from years of hours of flying operations.

That, when a "WASP" or "HORNET" owner has his engine serviced or overhauled he is assured of the same painstaking care and high quality workmanship that is used in the construction of the engines of the factory.

At each station a complete stock of parts is carried. For quick delivery our dealer can ship your order by air or to your place by rail. All Pratt & Whitney engine owners should fly to the nearest service and parts dealer for periodic inspection and overhaul.

THE
PRATT & WHITNEY AIRCRAFT CO
HARTFORD • • • CONNECTICUT
Division of United Aircraft Corporation

Manufactured in Canada by The Canadian Pratt & Whitney Aircraft Co., Ltd.,
Lumpkin, Quebec in Commercial Service by The Sevenwater Works, Montreal

Wasp & Hornet Engines

PRATT & WHITNEY AUTHORIZED PARTS AND SERVICE DEALERS

Location	Name
Chicago, Ill.	Universal Aviation Corporation
St. Louis, Mo.	Universal Aviation Corporation
Kansas City, Mo.	Universal Aviation Corporation
Wichita, Kansas	Universal Aviation Corporation
Brownsville, Texas	Pan American Airways, Inc.
Columbia, South Carolina	Pan American Airways, Inc.
Los Angeles, Calif.	Whitcomb Air Lines, Inc.
San Francisco, Calif.	Whitcomb Air Lines, Inc.
Tulsa, Okla.	Continental Air Field Express, Inc.
Omaha, Neb.	Boeing Air Transport, Inc.
Cleveland, Ohio	Boeing Air Transport, Inc.
Indianapolis, Ind.	Boeing Air Transport, Inc.
St. Paul, Minn.	Boeing Air Transport, Inc.
Seattle, Wash.	Boeing Air Transport, Inc.
Portland, Ore.	Boeing Air Transport, Inc.
San Francisco, Calif.	Pacific Air Transport, Inc.
Los Angeles, Calif.	Aero Corp. of California, Inc.
St. Paul, Minn.	Aero Corp. of California, Inc.
Denver, Colo.	West Air Service, Inc.
Cleveland, Ohio	West Air Service, Inc.
St. Paul, Minn.	West Air Service, Inc.
Wichita, Kansas	Pan American Airways, Inc.
Hartford, Conn.	The Pratt & Whitney Aircraft Co.
Lumpkin, P. Q., Canada	The Canadian Pratt & Whitney Aircraft Co., Ltd.



AVIATION

THE OLDEST AMERICAN AERONAUTICAL MAGAZINE

A McGraw-Hill Publication

ESTABLISHED 1911

EDWARD F. WARNER, Editor

VOLUME 1 . . . October 26, 1929 . . . NUMBER 1



The Scylla and Charybdis of Government Regulation

FOUR YEARS AGO the airplane industry was taking in Washington a unique lesson. Congress had been long accustomed to high-powered propaganda aimed at the establishment of regulatory legislation or the escaping of its effects upon commerce. Scylla if ever before had the accredited representatives of great manufacturing interests come before the committees of House and Senate and implored the government to take them in hand and put restrictions upon their activities.

In 1925 there was too little regulation, and the industry sought more. In 1929 there began to be alarming signs that too much may be imposed, and the industry prepares to struggle against that peril as it had once to struggle against the disastrous results of complete laissez-faire.

The Interstate Commerce Commission was created to regulate the railroads. The airlines, say the enthusiasts for regulation, are commercial and they are interstate. Why not turn them over to the Commission? Senator Brewster of New Mexico proposes to act upon the inspiration. There lies in the Senate a resolution introduced by him a month ago asking for an exhaustive investigation of airplane accidents by a Senate committee with the final object of determining "the feasibility and advisability of placing them subject to interstate air commerce under the supervision of the Interstate Commerce Commission, and if so, the kind and amount of legislation needed to accomplish that result." Vigorously opposed by Senator Duggan, the Senate's only qualified pilot, and debated to the extent of seven pages of the Congressional Record, the resolution was finally returned to the calendar without action. "It will come up again, and others like it will be introduced repeatedly. The industry must be prepared to meet the situation."

The subject of economic regulation, and especially of rate control, is too large to be treated in so general an editorial as this. We shall turn to discuss it again, and no doubt repeatedly, in the future. Concerning one pro-

posed change in regulation, however, the issue is clear enough to be disposed of at once. Upon any suggestion of taking the present technical functions of the Interstate Commerce Commission, and leaving their seat to the Interstate Commerce Commission, which are now the province of a whole well-sharpened knife, the Commission's functions are primarily economic and legal. It has no organization for controlling the airworthiness of aircraft. Equally clearly, there is no occasion for a Senate inquiry into so technical a matter. It would labor under an even greater handicap than did the Senate committee investigating the causes of submarine sinkings, and would accomplish exactly the same results—to wit, nothing. Associated interests should present a united front in opposition to any such suggestion. Upon that ground alone, the Duggan resolution should not pass.

//

Effort Sadly Misdirected

WORLDWIDE and national records are the first sort of publicity for aviation, or for any manufacturer of airplanes and power plants—provided that they are the right sort of records. Round figures which show some relation to practical conditions of operation testify to the quality of the equipment with which they are made and to the quality of the design and research that stand behind the other products of the same firm. Records which are mere statements of physical endurance or of unreasonable chance-taking ought to have no advertising value among intelligent people. They have no more to do with the progress of aviation than the late widespread cheapness-by-long-distance gambit had to do with the art of aviation.

The greatest offender against common sense is the solo endurance record. Airplane duration records are of the utmost importance, and we should like to see some Americans make serious attacks upon the present Common mark, but the endurance of the airplane has now

outspend anything that a single individual can hope to attain. With a crowd already standing at thirty-four hours a two-run crew is absolutely content to any means attempt to raise it. The first plane and engine to fly without stop and without refueling for three full days and nights will deserve and receive world-wide applause. To have flown a shorter time with the pilot alone in the plane is, for the airplane, no achievement whatever. It demonstrates nothing except some individual's ability to stay awake, by the use of drugs or otherwise, for an abnormal length of time at a rather monotonous task. The performance is one easily on a level with the dance marathons which have served in recent months to give depressing evidence of the number of sleep-winded business men in the land.

This may seem strange language. Strong language is called for. Solo endurance trials have already ceased at least one death, and they are sure to cause more if continued. Not only do they furnish us not as to the qualities of the airplane, but the worst airplane actually has the best chance. The danger that the pilot flies is not fatigue from overwork, but the inevitable sleepiness of monotony. It is far easier to stay awake for thirty-six hours or more in a machine that requires constant and varied action on the controls than it is to stay that the pilot has only to sit in his seat and watch it go.

Responsible bodies, such as the National Aeronautics Association, ought to be insistent that attempts at such records of this sort for prescription along with plane-changing and delayed-opening procedures, competitors. Responsible people seriously concerned with further development of aviation will have nothing to do with them. If publicity be withheld from the records of no value or those probably harmful, and if public applause for their makers be discouraged, there will be more effort to spend in directions where it can be of some use both to the aircraft industry and to aeronautical science.

//

Coming From the U.S.S.R.

THE UNITED STATES has a new group of aerial visitors. They are unique in two respects. They are the first who have ever entered the United States from Asia by heavier-than-air craft. They are the first who have ever come to us by air from Russia.

The crossing of the Bering Sea, and the flight through the Alaskan chain and Alaska, is a large undertaking at any time of year, and no matter how much preliminary organization may have been provided. To start off so short a time before winter makes itself felt, and with practically no preparation of any kind, bespeaks the implicit confidence of the crew both in their airplane's quality and in their own. In this case our scanty preliminary misbegotten and delays the confidence

proved itself justified when the expedition arrived on more hospitable soil. That last phrase can carry a double meaning. Not only is the climate of the continental United States much more friendly to visitors of every nationality than is that of the far northern Pacific, but the social climate is much less cold than it would have been for Russian visitors a few years ago. Without wishing to revive any unpleasant memory, it is worth recalling that when the Army's round-the-world fliers were forced to make a detour at Komsomolski five years ago they were given very short shrift by the local commandant, and orders came from Moscow to compel them to be on their way immediately. The greatness of the change since that time is sufficiently shown in the warmth of the welcome given to Messrs. Shostakov, Bolotov, Berlingoff, and Pufanov on their arrival at Seattle, a recognition that will be duplicated elsewhere in this country, and in the very good treatment rendered by the Ford plane now visiting Europe when it reached Moscow in its itinerary. Aviation, which is the greatest foe of isolation of spirit, has had its share in producing the change. The whole world applauded without distinction of nationality while the Russian and the Russian airplane pilots were waging their Russian struggle to save the Army's Halls of fame.

No one should take exception to the new state of affairs. The economic philosophy upon which the Soviet state is built, and the views of Vladimir Lenin which are there held sacred, happen to be alien to most Americans, but that has nothing to do with the case. Neither has the fact that our government has found it unexpedient to enter into diplomatic relations with the powers at Moscow. All that matters to us is that the officers and crew of the Russian-built plane "Land of the Soviets" are brave and skillful men. We shall examine their machine with interest as the original product of a national aircraft industry of the development of which we have known too little. We applaud their flight. We are sincere in our expression of hope that they will have only pleasant recollections of their visit to the western hemisphere.

//

Forestalling the Used Plane Problem

THE PRACTICE of trading in used planes on a new plane purchase is rapidly increasing. As the production of aircraft overtakes the demand it will become necessary more and more often to take a used plane in trade before selling a new plane. Distributors in the Southern California territory report that it is even now necessary to take in a used plane in full half of the new plane transactions, whereas a year ago these same dealers were selling nine out of ten airplanes without having anything about a used machine. At this rate

October 20, 1929

it is evident that in a very short while a new plane sale without trading a used plane allowance will be a very rare thing. The result is that needs of used planes are, rapidly increasing, and the problem of used plane disposal, trade-in allowance, re-conditioning, re-expression by Federal authorities, and final resale are becoming serious.

If the aviation industry is to avoid the trouble-prone which has become such a source of anxiety in the automotive world immediate attention must be given to this situation. If used planes are to be properly re-conditioned we must have more uniform shop practices. Factory branches at strategic points, or strong distributor organizations where factory methods are in vogue, will help to balance the buyer's confidence in a used plane purchase. The situation plays into the hands of the price gougers, for it forecasts a day when the small and lonely flyshop without powerful alliances will be unable to compete with the largest organizations which can render more complete service. This will result in a stronger aviation industry, and one in which "cheap" airplanes will be a rarity, because the surviving aircraft builders will be those who can stay in the game year after year, following the career of each individual airplane produced by that factory, and giving each airplane the service which will keep it in the air.

Of course the question of when a used plane has been properly re-conditioned, and when it has reached the end of its useful life, rest directly in the hands of the Department of Commerce, Aeronautics Branch. As other states follow the lead of the twenty that have already sold and take all aircraft out of the sky unless licensed by Federal authority, the Department's burden will grow heavier. It is to be hoped that Congress will provide funds for the proper expansion of the inspection branch, so its work now continue to be intelligently and comprehensively done.

Most important of all phases of the used plane problem is the need of the dealer to keep trade-in allowances low enough to leave a ample margin for the proper re-conditioning of the used airplane and no more at a price low enough to attract a buyer and high enough to insure against loss to the dealer. Dealers who grow more showrooms on old machines in order to make new plane sales are not being fair to themselves, the manufacturer of either the new or used plane, or the industry. Such a course can only result in cluttered used plane markets and stagnation within the industry.

//

Horsepower Versus Man Power

THE ACHILLES HEEL of the seaplane has always been maneuverability on the ground. From the first days of the first Zeppelin, the most serious moments

have occurred in getting the ships out of their hangars and in again. Even after a technique had been developed to the point where maneuvering no longer constituted a serious hazard of operation, it continued to impose a very substantial economic barrier to putting the ships into any regular service.

Trials of a mobile mooring mast made at Lakehurst within the past couple of weeks, have more practical bearing upon the future commercial employment of rigid airships than anything else that has happened since the British first introduced the high mast. The flights of the Los Angeles and the Graf Zeppelin have done much to speed the day of commercial employment, but there is nothing in the performance of these ships of the feasibility of which any competent authority was previously in doubt. That airships can be constructed to fly for ten thousand miles without stop, pass through very severe weather, and to make speeds of eighty miles an hour or better has been attested for a long time. There has been no assurance that they could be handled at their terminals with reasonable promptitude and at reasonable cost.

The high-mooring mast was the first key to the dilemma of ground handling, and offered the first hope of obviating the necessity of closing out the standing area to drag the ship into the hangar after a landing. The mobile mast just tried at Lakehurst, after many months of delay in its construction, is the second step in the same direction although for another purpose. The mooring mast often assumes of temporary helpings. The mobile mast makes it possible to get into the hangar and out with a minimum ground crew. The two supplement each other, for although the mooring mast is often sufficient to assist in a safe release, the hangar mast be available as a resort in case of damage to the ship or in severe storms, and it must be possible to take shelter without delay. A mobile mast, moving freely along a track and dragging the airship after it by the nose, both simplifies the process of docking and makes it possible to carry it out when it could not have been done at all by usual means.

This experiment developed by Commander Reestadt and his associates for purely naval purposes, resolves one of the principal factors which might have justified timid regard in looking away from commercial airship operation in the past. In accordance with the trend of the times, specialized machinery finds another opportunity of replacing human labor. Sociology may sometimes look with alarm upon the advance of the machine and its so-called supremacy over the man, but we may be sure that none of the critics even at Lakehurst, who have been turned out of all at all hours of the night to drag the Los Angeles into harbor, or who have stood by ready for action throughout nights when the ship did not come in at all, will join in deploring the introduction of a mechanical device to relieve them of the greater part of that task.

AIR ROUTE Radio Services

IN GREAT BRITAIN

By C. B. CARR

Editor of the British Air Ministry Special Staff



Whether the definition of the National Air Ministry Special Staff

Radio has come into its own in American air transport only very recently. It has been a regular adjunct to passenger services in Europe for a considerably longer time. Now that the importance of proper and continuous communications is universally recognized, European radio experience has a special interest for American operators. Mr. Carr describes it from a British point of view. The rental of radio equipment from the manufacturing company and the making of payment for its use as a basis of actual performance is especially interesting.

tion, that of the radio services is probably the most truly international, even unfortunately—lives many points of view—radio transmissions, once started, take no heed of national or other boundaries. Hence the closest international collaboration is required, in order both to present the services of one country from seriously conflicting with those of its neighbors, and to present the development of a common and what has now become an extremely complex radio organization.

Lately this fact was realized early in the development of air route organization in Europe; in 1919, representatives of many European and extra-European countries met in conference in order to draw up regulations which should be the basis of all air route operations in the countries concerned. The result of this conference



A general view of the transmission building, at the London General Post Office station

was the formation of the International Convention of Air Navigation, which was almost immediately ratified by all present who were party to the Conference, and which has, up to the present, been ratified by some 27 nations. The work of extending the scope of, and amending from time to time the original Convention, in order to keep abreast of the rapidly growing complexity of air route operations, is entrusted to a permanent commission, The International Commission of Air Navigation, which has its headquarters in Paris, and which meets at least once a year for this purpose at various European capitals in turn. Among other matters (such as air route and airport rules, meteorological, medical matters, etc.) this Commission deals, by means of a technical sub-committee with the regulation of air route radio services.

REGULATIONS adopted by the International Commission of Air Navigation are necessarily wide in their conception and their application. In order, therefore, to provide a means for dealing with the more detailed aspects of air route organization, recourse is necessary to smaller and less formal international conferences, or, where suitable international channels do not already exist, to direct collaboration between the countries concerned. The most important since international gathering of this nature is undoubtedly the International Air Traffic Conference, which meets twice a year, and which is attended by representatives of the governments of Great Britain, France, Belgium, Holland, Switzerland, Germany, Czechoslovakia and the Free Territory. The work carried out by this conference in regard to the provision of an adequate international radio organization for commercial air routes cannot be overestimated, since without such close collaboration on the part of the countries in question, the development of such an organization would have been impossible.

Ground radio stations in Great Britain for air route purposes are, as in other countries, forming party to the International Convention of Air Navigation, provided and operated by the government. No charge is made for their use by any aircraft, whatever its nationality, which

communicates with them, with the sole proviso that all communications must be confined to messages affecting the safety of the aircraft or the regularity of the air service. Although this proviso is purposely capable of a wide interpretation, it is not, in practice, abused, since the interpretation lies, on the one side, in the hands of responsible government employed ground station personnel and, on the other, in the hands of the pilot or operators on board the aircraft. Both of the latter hold government-granted licenses to operate radio apparatus in the air, and are accordingly liable to having their licenses suspended or even withdrawn in the event of repeated infringements of the regulations.

Aircraft registered in Great Britain and flying far from or beyond, if capable of carrying ten or more persons, including the crew (according to their Certificate of Airworthiness), are compulsorily fitted with wireless apparatus; the regulations governing this matter (purposely) tend to state whether radio telephony or radio telegraphy apparatus is to be fitted, since this is a matter entirely dependent on the conditions obtaining at any particular air route such as the seating capacity of the aircraft employed, the type of country over which the route passes, the distance apart of the route ground radio stations, the weather conditions normally to be expected along the route, etc. If radiotelephony is employed as the means of communication, the pilot himself acts as operator and holds a certificate and license to this effect; if, however, radiotelegraphy is employed, a fully certified and licensed operator is carried on board the aircraft for this purpose. In British aircraft, as in the case of the majority of European countries, the former state of affairs obtains on account of the severity (in reducing the payload) by its attendant amount as possible, in other cases, however, notably in the case of German aircraft a separate radio operator is carried on board, and radiotelegraphy employed as the means of communications.

British ground stations for air route radio purposes are accordingly capable of dealing with both types alike, in addition to the services operated by Imperial Airways, Ltd., French, Belgian, Dutch and German services

TO GIVE a comprehensive and accurate description of the radio services operating in Great Britain for commercial air route purposes is a task of some magnitude, owing to the complexity of the subject. Because of the fact that so much of the air route work with which Great Britain is concerned is of an international character, no account is necessary for beginning such an article with a brief description of the international aspect of air route radio services, as conducted in Europe, before describing in greater detail the radio services and organization as present operative in Great Britain—particularly note the latter are, to a great extent, regulated by international agreement.

Many European countries are relatively small in size, are comparatively densely populated, possess highly developed networks of railway services, and, in addition, suffer from winter conditions which are changeable in character and which, inevitably, make the regular operation of air services a task of great difficulty. The resulting tendency in the development of European air routes is for the services to be operated over distances of some length, and hence to become international rather than national in character. The task of organizing air routes is accordingly one which, in comparison with a similar task in a country of the size of the United States, bristles with administrative difficulties. Even a comparatively short air route may involve three or more countries and hence require the cooperation of a similar number of entirely separate national administrations in order to ensure a smoothly-running organization for the route as a whole.

Of all the aspects of international air route organi-

operate daily to and from the London airport at Croydon. Croydon is the terminal in Great Britain for international air routes, and the British government has recently installed at this airport, to replace the original radio station which was erected in 1920, one of the most up-to-date and efficient air radio relay stations in the world. In addition, a lower-powered relay station is installed at Lympne airport (near the English coast of the Channel) and a third station, the duties of which are solely confined to direction-finding work at Falmouth in Norfolk. These three stations provide all necessary radio services in connection with commercial air routes operating in Great Britain, and their functions can be conveniently classified under three main headings: (1) communication with the aircraft themselves (the aircraft service), (2) inter-airport communications (the "route traffic" service), (3) meteorological communications.

The aircraft service is carried out on a normal wavelength of 900 meters, both for radiotelephone and for radiotelegraphic communications, and comprises both the normal communications service to and from aircraft and the direction-finding service. In addition, in order to relieve the congestion which is already being felt on the 900-meter wave (owing to the large number of radio field aircraft which are in the air simultaneously, as a relatively small area of alternative wave of 900 meters is provided for radiotelephone communications, and use of 870 meters for radiotelegraphic communications).

Under the heading of "normal communications" fall the usual messages sent to and from aircraft operating along a typical air route. Ordinarily there is a first call, leaving the whereabouts of departure, in which the registration markings of the aircraft (which, incidentally, form its call sign) and the airport at destination are given, and by means of which the transmission wavelength of the aircraft is corrected if necessary. Then there are several messages reporting the progress of the aircraft along the air route, sent from pre-arranged points; requests for weather conditions ahead of the aircraft, if, as is often the case, these have changed materially since the departure, and a final message to

the airport of destination stating that the last recognized position-reporting point along the route has been passed, and that the aerial is being wound in and the aircraft radio station is closing down. In addition, special messages may be sent, such as requests from the pilot for instructions from the operating company's airport manager, requests from the pilot for assistance in case of trouble, messages from the ground authorities to a pilot, warning him that other aircraft are in his vicinity, during conditions of fog or low clouds, and so on. In this connection it may be of interest to note that in Europe the country is divided into areas for radio and ground control purposes; the definitions of these areas are agreed internationally, and each area has allotted to it an airport ground station responsible for communications



Reception apparatus in the Croydon Administration Building

with all aircraft up to the limits of the zone. For example, an aircraft flying within area "A" will communicate solely with area "A" ground stations. On passing from area "A" to area "B" it reports this fact to both area "A" and area "B" ground stations, whereupon the latter takes over responsibility for communications. It has been proved in practice that this system is both logical in conception and simple to operate. It has the great advantage that control of aircraft is systematic, and obviates the possibility of communications being carried out between aircraft and distant ground stations—communications which, as a result of the necessity for frequent repetition owing to weak signals, cause great disturbance to other aircraft working.

The aircraft direction-finding service, which is also operated on the 900 meter wave, is provided by a network of ground direction-finding stations. By means of



The newly constructed Administration Building at Croydon, showing the radio building

AVIATION

October 26, 1929

AVIATION

October 26, 1929

that service, the pilot of the last recognized position-reporting point along the route has been passed, and that the aerial is being wound in and the aircraft radio station is closing down. In addition, special messages may be sent, such as requests from the pilot for instructions from the operating company's airport manager, requests from the pilot for assistance in case of trouble, messages from the ground authorities to a pilot, warning him that other aircraft are in his vicinity, during conditions of fog or low clouds, and so on. In this connection it may be of interest to note that in Europe the country is divided into areas for radio and ground control purposes; the definitions of these areas are agreed internationally, and each area has allotted to it an airport ground station responsible for communications

with all aircraft up to the limits of the zone. For example, an aircraft flying within area "A" will communicate solely with area "A" ground stations. On passing from area "A" to area "B" it reports this fact to both area "A" and area "B" ground stations, whereupon the latter takes over responsibility for communications. It has been proved in practice that this system is both logical in conception and simple to operate. It has the great advantage that control of aircraft is systematic, and obviates the possibility of communications being carried out between aircraft and distant ground stations—communications which, as a result of the necessity for frequent repetition owing to weak signals, cause great disturbance to other aircraft working.

The aircraft direction-finding service, which is also operated on the 900 meter wave, is provided by a network of ground direction-finding stations. By means of

that service, the pilot of the last recognized position-reporting point along the route has been passed, and that the aerial is being wound in and the aircraft radio station is closing down. In addition, special messages may be sent, such as requests from the pilot for instructions from the operating company's airport manager, requests from the pilot for assistance in case of trouble, messages from the ground authorities to a pilot, warning him that other aircraft are in his vicinity, during conditions of fog or low clouds, and so on. In this connection it may be of interest to note that in Europe the country is divided into areas for radio and ground control purposes; the definitions of these areas are agreed internationally, and each area has allotted to it an airport ground station responsible for communications

with all aircraft up to the limits of the zone. For example, an aircraft flying within area "A" will communicate solely with area "A" ground stations. On passing from area "A" to area "B" it reports this fact to both area "A" and area "B" ground stations, whereupon the latter takes over responsibility for communications. It has been proved in practice that this system is both logical in conception and simple to operate. It has the great advantage that control of aircraft is systematic, and obviates the possibility of communications being carried out between aircraft and distant ground stations—communications which, as a result of the necessity for frequent repetition owing to weak signals, cause great disturbance to other aircraft working.

The aircraft direction-finding service, which is also operated on the 900 meter wave, is provided by a network of ground direction-finding stations. By means of



Interior view of the Croydon building showing floor & air terminal airport ground communications

once in two hundred miles of flight, solely as a result of the navigational assistance afforded by this service.

An additional service, with which the pilot of an aircraft does not come into such direct contact, but which, nevertheless, is of vital importance to the regular operation of air services, is the inter-airport, or "route traffic", radiotelegraphic service, which is operated on a wave length of 1360 meters, with an alternative wave of 1270 meters. This service (which is international in character, since all communications between aerodromes in Great Britain are carried out by means of private telephone lines rented from the Postal Administration by the Air Authorities) is used solely for the purpose of exchanging "enroute" messages between the Government authorities in the various airports; for example, immediately an aircraft leaves Croydon for, say, Paris, a departure message is sent from Croydon wireless station to the wireless station for Paris (La Bourgas), in which is given the registration marking of the aircraft, the name of the pilot, the time of departure, the number of passengers, and details of the freight carried. Similarly, immediately an aircraft lands at Croydon, an arrival message is dispatched by wireless to the last aerodrome at departure of the aircraft, in which is given the registration marking and time of arrival of the aircraft. In addition to the exchange of these routine arrival and departure messages, the inter-airport service is utilized for notifications in neighboring systems of obstructions to a particular airport, such as floods, snow, etc., for notifying instantaneous changes in service (delays, etc.) and, in general, for sending any message necessary to ensure the smooth-running and regularity of the air services. This service, like the aircraft radio service, is operated free of charge by the Government, and is subject to the same proviso as regards the types of messages which may be conveyed. In order to reduce the volume of traffic handled daily by this service, it has been found necessary to prepare an international code for abbreviating messages.

Still another service, with which the pilot of an aircraft rarely comes into contact, is that provided for the radiotelegraphic broadcasting, at regular intervals during the day, of meteorological information covering areas

WHERE IT IS stated that it is usual to give a pilot the position of his aircraft correct to within a mile or so, the outstanding importance of the direction-finding service becomes apparent, both from the point of view of the safety of the aircraft and its passengers, and of the increased regularity of the service which becomes possible; numerous cases could be quoted in which pilots have safely brought their aircraft through fog, sometimes without having been able to see the ground

served by the routes. This service, which operates on the wave length of 1200 meters in Great Britain, and on wave lengths of 1288 and 1316 meters elsewhere in Europe, is the nerve center of an exceedingly complex intercontinental meteorological organization, whereby the meteorological staffs at airports are enabled to prepare their weather charts, etc., at frequent intervals, usually every half hour or so, and to make their air route forecasts. The necessity for the utmost punctuality and regularity in the exchange of meteorological information is obvious, and the importance of this air radio service to the successful operation of commercial air routes cannot be over-emphasized.

The station at Crofton is worthy of special note. It comprises a receiver group, which is situated on the flying field, and a transmitter group, which is situated at Mithras Common at a distance of slightly over three miles from the airport. Each receiver group consists of a hand-cranked pump, the two groups, one or more transmitters. The receiver group consists of a direction-finding receiver for the aircraft service, operating on a wave-length of 900 meters which is installed in the Control Tower, and a second receiver, for the inter-airport service, which is non-directional, and is installed in a room in the Administrative Buildings. It operates on a wave-length of 1280 or 1210 meters.

The transmitter group comprises four 4-kw. telegraph-telephone transmitters installed in a building which is specially designed for this purpose. These transmitters are identical in characteristics, each being capable of transmitting continuous and interrupted continuous wave telegraphy, as well as radiotelephony, on any wave-length between 800 and 2000 meters. In addition, each transmitter is provided with an "independent" system of tuning in order to ensure the efficiency of transmission frequency. At present, two of these transmitters are employed to furnish the aircraft radiotelephony and aircraft radiotelegraph service respectively, a third is employed to furnish the inter-airport radiotelegraph service, and a fourth is kept as a "stand-by," being capable of any device at any of the other three in the event of trouble. The meteorological service is at present carried out by the British Air Ministry Wireless Station, but it is possible that in the near future this service also will be operated from the Crofton station. The equipment for both the transmitting and receiving group was designed and supplied by the Marconi Company of Great Britain and has given complete satisfaction in every respect since its installation some eighteen months ago.

THE TYPE OF INSTRUMENT standardized for use in British commercial aircraft is the Marconi type A264 130-watt "Universal" aircraft telegraph-telephone set. The transmitter and the five valve receiver are enclosed in a common instrument case. The transmitter can operate on any wave-length between 800 and 1500 meters which installed in a passenger-carrying aircraft, and the receiver on any wave-length between 200 and 1800 meters under similar conditions. The remainder of the equipment forming the complete installation comprises a hand-driven generator (provided with an automatically switchable pitch mechanism), which supplies both aro and fluorescent power to transmitter and receiver valves; a six-volt accumulative battery which "feeds" across the low-voltage output of the generator; an automatic type of aerial switch, a trailing aerial 200 ft. long; the filarfil, through with the aerial wire passes on its way between

the aerial wrench and the antenna of the fuselage; a head set, consisting of a pair of telephone receivers and a microphone with a special helmet containing (fitting to take the telephone receivers) and the necessary cables. If an operator is carried and radiotelegraphically employed as the means of communication, a telephone set is supplied, together with additional equipment for providing telephonic inter-communication between pilot and operator. The instrument case is arranged for remote control by means of Bowden cables from the pilot's (or operator's) seat, in order to simplify installation. The Marconi Company keeps a staff of skilled engineers and electricians whose telephone duties consist of inspection and maintenance of the aircraft wireless equipment. The same type of set is used on Belgian, Dutch and Swiss planes.

The weight of the complete equipment as described above is slightly over 100 lb., and the maximum two-way radiotelephony range from Crofton airport radio station is 250 miles; the radiotelegraph range from Crofton under the same conditions is on the order of 400 miles.

THE CONTRAST between Imperial Airways and the Marconi Company is drawn up on the basis of "payment by results"; flights which are successful, from a sales point of view, are paid for according to mileage flown, and any flight on which radio communication fails or unsatisfactory or completely unsuccessful fails to rank for payment. Since the most successful of successful flights is carried out jointly by the two Companies (cases of doubt being settled by reference to data supplied by the Crofton wireless station log-book) it follows that this system not only provides the fairest basis of payment as between the Companies in question, but also serves as a means of obtaining and collecting and thoroughly reliable data as to the efficiency of the British aircraft radio service. During the year 1938 the figure for successful flights as compared with unsuccessful radio communication during flights averaged 99 per cent, and the total aircraft miles during this period was approximately 782,000 miles. This stage of efficiency has been reached in only nine years of operation.

In conclusion, a few data concerning the work carried out by Crofton wireless station may be of interest. During the week ending Aug. 1, 1939, but excluding a typical summer week so far as air services are concerned—radiotelephony communications were carried out with aircraft employed in the operation of 296 separate air services, and radiotelegraph communications with aircraft employed in the operation of 112 air services. In addition, 78 weather reports were sent to aircraft. Owing to the fact that no record is kept of the total number of messages passed between Crofton radio station and aircraft, and vice versa, an accurate figure in this respect cannot be given. On the assumption, however, that each air service operated involved the sending of at least five messages from the aircraft to Crofton, and neglecting messages originating from the ground, it will be seen that more than 1500 messages are sent weekly in the aircraft radio service.

During the same period the inter-airport service handled 825 "m" messages, totaling 11,223 words or 722 "m" messages, totaling 6,243 words—figures which demonstrate most clearly that this service is of almost equal importance to that of the aircraft radio service in the regular operation of commercial air routes.

THE GENERAL Mailplane

By LIEBIG E. NEVILLE

Technical Editor of AVIATION

THE MODEL 108 MAILPLANE, developed by the General Aircraft Corp., Buffalo, N. Y., is now to be manufactured on a quantity basis. Flight tests are now being conducted and production tooling installed at the factory. Credit for the design is due A. Francis Armer, Vice-President, in charge of operations of the company and Roscoe I. Markey, project engineer. The airplane whose principal data consist of inspection and maintenance of the aircraft wireless equipment. The same type of set is used on Belgian, Dutch and Swiss planes.

The Model 108 is a monoplane having an open cockpit in the rear portion of the fuselage with the mail compartment occupying the entire forward portion. By a few simple changes in the mail compartment construction the plane can be converted into a passenger transporter. The power plant includes a Pratt & Whitney geared Hiram engine rated 325 hp. at 1,900 r.p.m.

Aluminum alloy is employed throughout the construction of the fuselage which is of the monocoque type. Wood is used only in the wing beams which are box type built up of spruce. The wings and tail group members have fabric covering. The Model 108 has a span of 50 ft., an overall length of 35 ft. and an overall height of 11 ft. 11 in. The weight of the first phase empty including 340 lb. of special electrical equipment was 3,280 lb. and the gross weight 6,000 lb., giving a useful load-gross weight ratio of 0.92 by displacing the weight of special equipment.

The high value of this ratio is attributable to a large degree to the positive disposition of material in the structure. In general, overall dimensions of structural members have been made as large as possible within the limitation set by the danger of failure by cracking. The characteristic is noted not only in the fuselage and

wing boxes but it is also to be observed in many of the tubular members in various parts of the structure. In practically every possible case, large diameter thin-walled tubes are used rather than tube members having comparatively smaller diameter and thicker walls. A thorough stress analysis verified by static tests has contributed in obtaining a rigid structure throughout.

Pull advantage has been taken of the stressing possibilities furnished by this almost elliptical fuselage cross-section which lends itself readily to the installation of cooling of the N.A.C.A. type. The aerodynamic efficiency has been further increased by fairing of sharp corner such as the intersection of lower wings and tail surfaces with the fuselage. In the case of the adjustable stabilizer, the cuffs or fillets are so designed that they move with the stabilizer. The wing and shear stress are fitted with removable fillet cuffs.

In order to provide the necessary propeller efficiency for a fuselage of so large a section, the geared engine was selected. This permits use of a large diameter slow speed propeller which is desirable where the fuselage section is large.

The maximum depth of the mail compartment is 60 in. and the maximum width, 26 in. One hundred and seventy-five cu ft. of cargo space is provided. An effort is made to reduce the width of the fuselage at the cockpit and at the rear line have sufficient width at the tail to provide a rigid installation for cargo cage members.

THE FUSelage construction of the first plane is an adaptation of the methods developed by the Hall Aluminum Aircraft Corporation, also of Buffalo. It is claimed, however, to make certain modifications in the production model. In the first place, the material



A rear view of the General Mailplane showing the distinctive lower wing and tail and protruding fuselage.

throughout was Alcoa's Company of America design 175T sheet stock. Alcoa will be used on future production models.

The structure consists of three solid die-cast bulkheads with 12 rib type frames. The frames were built by the Hall company and consist essentially of angle members capped with flanged tubes. Two types of stringers are used, and both are standard Hall design sections, i.e., a built angle and a flanged U-section. At the maximum span there are 34 stringers which provide ample support for the skin and prevent buckling of the shell. Skin is attached in 12-in. strips and riveted. Although the contour of the fuselage is gracefully formed, there are no lumped sections in the skin.

Several modifications of the method of fabrication are to be made in the production model. The frames are to be built in halves, left and right, making it possible to attach stringers to the skin while it is in the form thereby greatly simplifying the riveting operation. The skin in the production model will be applied in 24-in. strips instead of 12-in. strips as was necessary in the construction of the first airplane. Skin and frame are both reinforced by glass plate as required. Joints are treated in assembly to prevent corrosion.

The skin thickness, which is determined on the basis of static tests is currently proposed to meet the Department of Commerce requirements at the same time working at as high unit stress as possible.

The wall is reinforced by double diagonal stiffeners of flanged U-section. A casting of special design is placed at each of the four corners at the ends of the U-section members. This provides four points of suspension for the engine mount. The covering is designed to accommodate double rubber washers between its end-plate members, the whole being held together by a through bolt, to which the engine mounting members are attached. This special joint is effective in eliminating the engine vibration passing into the fuselage.

There are two doors in the fuselage: one on the top outer at the front end of the baggage compartment and the other on the left side at the rear. The top outer door is in the first plane in 28 in. diameter and will be riveted to 25 in. long by 25 in. wide with approximately a five-inch radius in the corners. The rear door is now 22 in. high by 36 in. wide and will be increased to 34 in. wide by 46 in. high with a 3-in. radius in the corners. This door will be placed in the right side of the baggage compartment instead of on the left. If the plane is converted into a six-passenger transport, eleven round windows, 12 in. in diameter will be added and the side door also will be fitted with a window. The door to the top would then be modified to serve as an emergency exit.

These wires have washed out tips which are characteristic of silver General Airplane Corporation design. The washed out incidence is intended to reduce tip losses and decrease the tendency to yaw. The lower wing is tapered in section only, with the characteristic tips. The tapered lower wing, washed out tip and small dihedral are employed to obtain a high degree of lateral stability. An airfoil section of medium thickness, designated G.A.C. 900, is employed.

Lower wing struts are built up of two beams of heat-treated chrome vanadium steel, attached to the fuselage by bolting to aluminum alloy castings riveted to

the fuselage structure. Rigidity of the bolted joints is maintained by tapered bushings. These tapered bushings are well used at several other points in the construction. At points of highest stress, where stringers are attached to the fuselage, steel rods or bolts are used in place of aluminum alloy rivets. This is true not only of the lower wing struts, but of the engine mounting, exhaust pipe fittings and tail wheel mounting. The beams are braced to the fuselage internally by steel tubes, and externally by struts made of wire. The steel bracing was not required by the designer but was employed to increase the rigidity of the structure. The struts have rib built up of metal angles, and braced by a Warren truss. Double struts made of wire are used in the plane of the left struts to increase the rigidity of the struts.

The wing structure is built up of spruce beams with aluminum alloy ribs. The four ribs are constructed of flanged tube section material braced with a Warren truss and riveted together, while the compression members are aluminum alloy round tubes with transverse wire bracing in the plane of the ribs. Compression members and wire bracing are double. The double tubes form a complete compression member, tied together at the ribs with aluminum alloy channels, to which steel lugs are riveted for the wires. These rivets also hold in place a cover plate which mates with a leaded plug at the end of the tube, keeping it in position and allowing for any contraction between beams.

The channels are attached to beams with eye bolts having heads so placed that they are used for loosening the transverse bracing wires in the plane of the compression ribs. By this means, it is possible to install or remove compression ribs without interfering with the form ribs. Plywood covering is placed in the lower surface of the first bay where the glider tests are mounted.


Each form rib is attached to the wooden beams by eight aluminum alloy angles, and by wood screws. Static tests showed that this method demonstrates any possibility of failure at this point. Wing beams are of equal length and a T-section end rib built up of spruce provides a stiff and durable tip. Internal bracing ac-



The engine mount, construction of the fuselage

October 26, 1937

October 26, 1937



ends to the tip. Steel and aluminum alloy have been used in construction of wing fittings according to the requirements of loads, considering serviceability and weight. Wing fittings of the column are of steel, while the strut fittings are of aluminum alloy.

Aluminum has full leading edge balance and differential action for upward travel being approximately twice that in the downward direction. A slot back into the wing just ahead of the strut was used in size with the change in position of the struts, the purpose being to increase the stalling angle. In construction the struts are similar to the elevator and rudder which will be described in detail later.

Each strut is mounted on five rubber cushions, members of aluminum alloy, which are bolted directly to the wing beams. The bolts run for this purpose are the same as those that hold the transverse wing bracing. Care has been taken to avoid crushing of the beam under the tips of the mounts by using large washer blocks, one adjacent to the beam and large steel washers under the legs of the mount. Adapters are prevented from shifting endwise by adjustable

bolts set in each end of the struts on the hinge axis. The loads of these struts fit against the reinforcing plates in the adjacent rib on the wing.

THE ENGINEERING is mounted on self-aligning ball bearings to prevent loosening that might result from elongation of bolt holes. The elevator and stabilizer are built in two halves and the connections are made with steel fittings, bolted together with bolts having the special wedge lockings. The stabilizer and fin have rectangular aluminum alloy boxes, aluminum alloy ribs and leading edge.

An inverted double cantilevered stabilizer section is used for the stabilizer. The section being rigid, permits use of rigid beams of large overall dimensions. The front beam is attached to the rear by a set of gusset plates. Ribs are built up of flanged tubing in the form of a Warren truss, and the end rib is reinforced with built angle material. This type of construction is also used in the vertical fin. The elevator and rudder are somewhat similar in construction to the ribs being identical to some of the fixed surfaces, while the beams are chrome molybdenum steel tubes with welded lugs to which the ribs are riveted. Beams in the movable surfaces are large diameter thin-walled tubes. The elevator halves are joined by a tube carrying a double root, the tube being attached to each elevator by a pair of bolts and wedged bushings of the usual type providing a tight fit. The roots are attached to collars, which are in turn riveted to the beams eliminating the necessity of welding directly to the beam of the elevator and rudder. As the case of the aluminum movable surfaces are AE leading edge balanced throughout the full span of the surfaces. Tail surfaces and aluminum were static tested with loads 25 per cent greater than design requirements, without a single failure and with unusually small deformations. The tail surfaces were designed to I.C.A.N. requirements, which, for this design, were 55 lb. per sq. ft. Vertical surfaces were designed to the same loading as the horizontal surfaces.

STABILIZER 36-in. by 8-in. or 40-in. by 10-in. Bendix wheels and linkages are employed for the leading gear which is of the divided axle type, built up of tripod tubes. Main axle tubes and bracing tubes are braced to the fuselage at the location of the double frames and connected to high strength steel castings carrying the axle shaft. Both ends of the shock strut and both pivot arms are fixed with replaceable bushings, the metals being braced to steel. The tubes are of heat-treated chrome molybdenum steel with aluminum alloy about flaring reinforced by the struts.


An unusual feature of the shock absorber unit is a combination of rubber and oil units operating in series.

The compressor rubbers have welded abrasive section and are built up in cellular form. The oil pump is fitted with a stuffing box and the plunger has a release valve to permit quick recovery of the hydraulic unit. Care is taken to prevent oil from coming in contact with the compressor rubber by insulating a wick order for the guide bearings in the compressor rubber seal. This oil can be quickly and easily refueled in service by connecting a filtered oil attached to the lower wing at the top of the strut. In landing, a total vertical deflection of ten inches is provided for the wheels, and five inches while taxing. This shock absorber unit is the result of a long series of experiments, and rubbers was selected to be used in connection with the also used to eliminate any positive and abrupt limit to the deflection, in order to avoid shock loads on the structure.

Another interesting feature of the landing gear is the self-aligning tail wheel. The wheel is mounted on a heat-treated chrome molybdenum steel tube fork in such a way as to permit 350 deg. swivel action. The fork is carried in a steel tube which protrudes to the fuselage on a horizontal axis and mounted on large diameter bear-

absorber strut in full universal joint mounted with cross bolts and the parking brake is adjustable. A total vertical deflection of 9½ in. is provided. An emergency shock bolt of a U section material and filled with hard wood is provided at the tail to furnish a means for a parking brake.

THE STABILIZER ADJUSTING MECHANISM is operated by a torque shaft from the cockpit fitted with universal disk universal joints. The shaft assumes a steel worm and bevel gear mounted in aluminum alloy cast housing, which is dust and waterproof. Provision is made for adjustment of the worm gear for wear. The gear is mounted in self-aligning ball bearings belted to our aluminum alloy fitting riveted to the skin. These fittings are kept in alignment by a transverse tie rigidly attached to each fitting. The linkage to the stabilizer is an independent steel mounted on ball bearings and attached to lugs on the fuselage beam of the stabilizer and is so designed that it does not transmit as well as virtual loads. It consists of a stainless steel center line of which travels through an arc of about 120 deg. The



Left—The steering arm connects wheel to fuselage and universal joint.

Right—Showing the adjustment of the steering arm ball wheel.

ings fitted with replaceable bearings. The stabilizer bearing contains a unique cone mechanism which centers the wheel. The fork is hinged to wing leading edge and is provided with an Alnico connection for lubrication. The internal cone is constructed on the upper end of the fork tube, which acts downward against a vertically sliding mating cone and coil spring. Any departure of the tail wheel from normal position causes the cone to compress the spring, while the reverse action of the spring against the cone keeps the wheel centered when the plane is moving straight forward.

The tail wheel was constructed in co-operation with the Westinghouse Electric & Manufacturing Company, and the Goodrich Tire & Rubber Company. The wheel is built of Mousira and is hollow and of full attention to form with a replaceable solid rubber tread. The wheel is fitted with a bronze bearing bearing on a replaceable steel sleeve belted in the fork by an aluminum alloy lock. A supply of lubricating oil is carried in the hollow portion of the wheel and holes are provided in the bearing for the lubricant to reach the steel sleeve. As the wheel turns a portion of the oil supply is carried upward and falls on the bearing, providing constant lubrication at that point.

The tail wheel shock absorber arm is also oil and rubber, but unlike that of the landing gear, the oil and rubber act in parallel rather than in series. The shock

absorber carries a double-link mechanism belted to the stabilizer beam. This connection works on the simple principle, giving greatest controlling power at the ends of travel when the stabilizer is subjected to the highest loading.

Self-aligning bearings are employed in the control system wherever it is desirable to reduce friction which may stress under load. Bearings in the control system are pushed with grease and kept waterproof by felt washers and metal pointers. Cartridges are used wherever necessary to provide seating for ball bearings in the control system, and special attention has been paid to their design in order to reduce friction.

The control stick is built up of two channels, and has a very wide base. It is light in weight and carries its load with a minimum of deflection. The connection of control stick to torque tube is ball bearing mounted.

The aileron control consists of a cast aluminum alloy ball crank, mounted on double ball bearings steel to maintain alignment and reduce friction. These bearings are mounted in a bracket of steel which is bolted to the wing beam. The ball crank, which is actuated by cables, is attached to the aileron by an adjustable connecting link resembling a turnbuckle.

Engine controls consist of push pull rods guided by fiber tubes, attached with ball and socket joints to ball bearings mounted ball cranks. Aluminum alloy levers mounted on a large diameter stainless steel tube are used for controlling the bearings. The levers slide between bakelite plates and friction can be adjusted by the pilot as any time by turning a large diameter knurled nut on the base of the control.

Special attention was devoted to the design of the instrument board, which is of aluminum alloy sheet and attached to one of the transverse frames by a shock-proof rubber tire mounting. The board is divided into three sections, of which the center is easily removed. Flight instruments requiring constant adjustment are mounted on this section. The right division carries pressure gauges and fuel control units, and by the means of the pipe lines are kept on the right side of the airplane. Controls for the electric system with all electrical grouped in one unit on the left portion of the board. Flight instruments, except the Mastermeter for Warning Indicator, were furnished by the Pioneer Company. An electric clock, manufactured by the Sterling Clock Co., also is included as standard equipment. Another feature of the instrument equipment is an electric tachometer.

Of special interest is a switch of new design, manufactured by the Bryant Electric Co. This switch has a carrying capacity of 35 amperes, and is mounted in a streamlined light weight bakelite case. Several type electrical switches for work requiring lower carrying capacity also are used. The flight instruments are so placed that a least light the pointers are in horizontal position. In a climb there is a general movement upward of the pointers, and in a dive the pointers turn downward. Two cord restraints are located at a convenient position on the board, one intended to accommodate the compass correction card, while the other is for brake

corde on which the pilot may make annotations while in flight. In the lower right-hand corner is a plate giving the major dimensions and weight of the plane, and also having space for the number and model, as well as the number of the approved type certificate.

The pilot's seat is adjustable through a range of 10 in. in vertical travel, a horizontal range of 4 in. and an angular range of 6 deg. The seat frame may be released quickly from the structure. The seat may be swung forward from the top, giving access to the rear portion of the fuselage and entering the door of the pilot's locker. This compartment, which has a capacity of 3 cu ft, is located in the fuselage behind the seat. Brake and rubber pedals are ball bearing mounted, and the brake is applied by an auxiliary spring hinged to the rubber pedals so such a point that the movement of the spring applying brake is not hindered by the angular movement of the pilot's seat.


An adjustable windshield is provided, having removable glass in the front, colored glass on the sides, and with flanged lugs on the edges on the side. The windshield is set in rubber, and rubber washers are used to provide friction for the adjustment.

THE NACA CONTROL which is well aligned to the design because of the fuselage section, is so constructed that it can be removed in sections and such action can be removed without disturbing the others. An electric inertia starter and booster coil, which are controlled by a single button are provided. Pushing the button winds the inertia starter and pulling it engages the starter and automatically applies the booster. An engine-driven pressure of 25-ampere rating and a 12-volt, 15-plate, 65-ampere-hour storage battery with the necessary recharging equipment, constitute the electric system.

Consideration of service details and an attempt to provide complete one-man operation, is characteristic of this design. Controls are provided on the side for a jack. Towing cables are furnished as regular equipment. The front wing struts are fitted with lugs to which tie-down cables can be attached and three corkboard emblems are furnished with each wingtip. The tie-down cables are fitted with sections of aluminum alloy tubes which make it possible for a man to stand on the ground and tension the cables in position without the use of a jacking ladder or other workhorses usually employed for a high wing.

The specifications as developed by the manufacturer:

Model	No. 10F
Purpose	Mail transport
Type	Open cockpit monoplane
Power plant	Coe Pratt & Whitney General Motors
Rated horsepower	300 at 1,600 rpm
Wing span (upper)	30 ft.
Wing span (lower)	27 ft.
Overall length	35 ft.
Overall height	11 ft. 11 in.
Tread	40 in.
Total wing area	452.4 sq. ft.
Wing loading	12.8 lb. per sq. ft.
Power loading	12.5 lb. per hp
Weight empty	3,360
(Load 340 lb. special electrical equipment)	
Disposable load	842.0 lb.
Pay load	400.0 lb.
Gross weight	3,760 lb.
Fuel capacity	135 gal.
Oil capacity	13 gal.
Mail compartment capacity	175 cu. ft.



The tail wheel assembly and shock absorber.

WITH THE *National Air* Tour

By JOHN T. NEVILL
Deputy Editor of Aviation

AS THIS STORY is being written the 1959 National Air Tour has progressed on schedule as far as Jacksonville, Fla. Johnny Livingston, piloting a Whitehead-powered Waco, is far in the lead on points, with a total of 19,981.78 chalked up to his credit. Second place is held by A. J. Davis piloting another Whitehead Waco, who has a total score of 17,863.50 to the good. Third place is being filled by a tri-motored Ford with two Whiteheads and a Wasp, piloted by M. E. Zeller. The total point score for Zeller is 16,784.68. The rest of the first 30 are as follows:

A. Fairchild KR, piloted by D. M. Haldeman, with a score of 16,629.84; a Bellanca, piloted by George Haldeman, with a score of 14,629.90; a Bellanca, piloted by R. A. Stagle, with a score of 13,725.27; a Commodore-Aero, piloted by Major Cone, with a score of 12,853.81; a Firebird KR, piloted by Mrs. Keith Miller, with a score of 12,574.08; a Curtiss Thrush, piloted by Dale Jackson, with a score of 12,118.40; and a Ford, piloted by B. S. Warner, with a score of 12,078.79. The remaining contestants in order of points are:

Ruby No. 38, 34, 31, 1, 46, 38, 25, 32, 25, 14, 24, 39, 18, 4, and 2. The 1959 Air Tour began with a short 15-mile hop across the Detroit River to Windsor, Ont. The jump to the first roundday stop at Walker Airport was made without incident, only one of the 29 competing craft falling in score to "figure of merit" for the leg. The entry, a Ford trimotor equipped with 2 Wasp and flown by B. S. Warner, failed to maintain the required average speed of 106.35 m.p.h., principally because of

the leg's brevity, which left him a few seconds below at least. A thorough entry in the Tour, a Bellanca C1250, which was on the field and ready to start, was withdrawn just prior to the start after it had coasted over and damaged a propeller during belated take-off and untimed tests on the morning of the take-off.

After having lunch on the airport at Windsor the Tour pilots took off for the 350-mile flight to Toronto, Ont., a course which took them over the little farmlands of the Province, a terrain which gave no hint of the bad country that was to follow. This jump was made with assistance from a helpful out-cast along the southern side of a large low-pressure area hovering over Hudson's Bay. This wind was replaced to a greater degree at an altitude of about 6,500 ft. and some of the pilots elected to take advantage of it. The Lockheed entry, the Commodore flown by Steve Lacey and Stanley Swenson, George Haldeman's Bellanca and Art Davis' Waco, made the best elapsed time into Toronto. Most of these planes, incidentally, with one or two others, were consistently among the five or six speediest craft on each leg. The Lockheed, flown by Wiley Post, covered the 350 miles between Windsor and Toronto in 1 hr., 33 min., 4 sec., an average of 170 m.p.h. Steve Lacey, negotiating the distance in 1 hr., 27 min., 50 sec. George Haldeman came next with 1 hr., 27 min. and 35 sec. Post and Lacey had each flown the 15-mile Detroit-Windsor hop in 4 min. 57 sec. Again only one entry failed to fly the course within the required time, Maple J. Carroll Cone, pilot of the Curtiss Challenger (scored

Commodore Aero, having gone off the course and lost time by having to get his bearings).

Following an average stop at Toronto, the planes took off from the Light Aeroplane Club field on Sunday morning and headed northward toward Ottawa. 238 miles distant. Over 700 miles the planes found, virtually the same weather that has assisted them on the previous day, although the day's flying found an increasing cloudiness that grew into an overcast sky at Montreal. The terrain was level, and the referee had advised being well to the south of the direct line, but few pilots did so. All of the planes landed in Ottawa in good time, the Lockheed again making the best time by flying the 238 miles in 1 hr., 17 min. and 53 sec. or 176 m.p.h. Lacey's score elapsed time was 1 hr., 23 min. and 12 sec., that of Carroll, 1 hr., 24 min. and 30 sec. The first finishes of the Tour was brought to light in Ottawa, Miss May Hendley, pilot of the American Eagle entry, having her head dressed for an injury, sustained in the air when something came adrift from the engine compartment and struck her. Ottawa was merely a lunch stop, and at 2 p.m. the Tour plane began departing on the 112-mile flight to Montreal.

Like the leg between Toronto and Ottawa the Ottawa-Montreal jump carried the pilots over scores of miles of wilderness where a landing might have been made only with considerable danger. On this leg a single direct tail wind obtained at about 6,000 ft., but few, if any, of the contestants checked that high due to the brevity of the leg. Every plane required perfect scores for the leg except the Traveler Air 6000A flown by Newman Windsor, who reported a line of pressure, constituting a reduction of his speed. Forty minutes and two seconds was the best time for meeting the 112 miles, that being chalked up by Wiley Post in his Lockheed. The next best elapsed time was Haldeman's, 40 min. 31 sec., Lacey's, 41 min. 15 sec., and Roy Wagoner's in the Hornet-powered Boeing 55, 44 min. 23 sec.

The Lockheed's average here was 166 m.p.h. It had so far been the leader on every leg.

A huge crowd, estimated at between 30,000 and 50,000 persons, was on hand at St. Hubert's Airfield, Montreal, to witness the arrival of the racing planes. This is believed to be the largest crowd ever to witness the arrival or departure of any National Air Tour. An air



Crowd at St. Hubert Airfield, Montreal, watching the Tour planes.

meet in progress on the Montreal airfield at the time undoubtedly nullified the theory to a number for in case of that which ordinarily would have awaited the Air Tour planes came in. Due to the unprecedented attendance at the airport and to the fact that only two-way road was open between the airport and the city, the two personnel, numbering more than 100 men and women, had great difficulty in getting into town. In most cases those on the Tour were here 3 to 5 hours reaching their hotel from the field, whereas, they had traversed the 112 miles between Ottawa and Montreal in one hour or less. The evening's banquet had to be postponed to nine o'clock.

DURING this winter in Montreal a series of moderate showers fell, which did not help the already wretched condition of the airport, although the weather had cleared, leaving good visibility and moderate tail winds, when the contestants reached the field the following morning. The 238-mile flight between Montreal and Portland, Me., incidentally, was regarded as one of the most difficult of the entire 5,000-mile route, principally because of the altitude required for negotiating the two mountain ranges between the two points, as well as the weather prevailing over land beyond those mountains.

Although the weather at Montreal was overcast, the reports and forecasts indicated probability of trouble ahead, and Captain Hawke estimated that the tour in full would be had down through to Portland and rephrased that the way was clear, just before the scheduled starting time there came a message that the weather was bad but possible and the first plane accordingly got away 50 min. minutes late.

C. G. Andrus, government weather bureau expert, traveling with the Tour in the to the second Ford, Standard II, equipped with radio and used as the Tour's "weather bureau," had warned the pilots of the probable weather and many of them carefully checked their navigating instruments before the start of this leg.



View of the Tour field at St. Hubert Airfield, Montreal, Me.

leg. This state of affairs, a delighted one from a book-keeping point of view as well as from the pilot's angle filed Arthur G. Schneider and E. P. Gooder, the Tour's very much overbooked owners with extreme optimism. But the operation was short-lived. The Washine Thompson plane was lost to the Tour on the takeoff at Richmond, the plane's engine quitting just after the wheels had left Legion Field. Donald Mither, the pilot, "let her down" with little injury to himself or the occupants of his craft, but with considerable damage to the plane. Another mishap occurred on the next afternoon, Men-Kin Miller ground-looping her Fairchild K24 upon landing in Richmond and breaking off the left wheel. The wheel, however, was replaced in short order, permitting the woman pilot to take off on schedule Thursday morning. Washine's Travel Air and Statton's Cessna were the only two craft to meet the 128 pilots and 1,000 passengers at Richmond and Byrd Field, Richmond, within their allotted time. The morning hop had been made under clear skies with light cross-winds, coming mostly from the northeast. In the afternoon there was very little wind of any kind. Hot clipped times recorded for the day's two flights were: (Richmond to Winston-Salem)—Lacey, 35 min 07 sec.; Post, 35 min 18 sec.; Davis, 35 min 30 sec.; Baltimore to Richmond—Post, 40 min 30 sec.; Lacey, 35 min 50 sec.; Livingston, 40 min 34 sec.; Davis, 40 min 19 sec.; and Wagner, 40 min 38 sec. Lacey and Lacey were the fastest, averaging 184 m.p.h. The pilots of the latter plane appeared to be keeping a little more in reserve than during the first days of the tour.

The Baltimore-Richmond hop was the tenth leg of the Tour's route.

Richmond's routine included a 385-mile hop down to Jacksonville in Winston-Salem, N. C., in the forenoon and a 152-mile afternoon flight to Greenville, S. C., where the night was spent. The first leg of the day featured a war-bird air show at the airport, which was held and cancelled the pilots to arrive the earliest possible. While the Warner-owned Cessna was kept on Byrd Field when Earl Statton, a pilot, who had been feeling badly for several days, was taken to a hospital. Later, the Cessna was brought on by Joseph Morrison, reserve pilot, who had been flying with Statton. Lacey's plane, "The Corbin-Corbin lost its position at 515 ft in the canopy" on the Richmond-Winston-Salem leg. A broken magneto shaft on one of the motors shortly after its take-off at Winston-Salem forced it to turn back and land at Richmond. Its passengers, including a woman, who was a sister-in-law of the next control point, where the Corbin was to park them up as soon as repairs were effected. A series of two or three landings involving various losses they were returning missed the passengers to spend the night on the road. They arrived in Winston-Salem early the following morning, dirty and weary and with a Hurricane tail to tell, but just in time to be taken aboard the Corbin and flown to Greenville. Another early left standing on the Richmond airport was the Stinson-powered American Eagle, flown by Fritz Hanley. This plane was kept in Richmond with minor trouble, but it was not to fly on the tour at Greenville before supper. Besides the Corbin, the Warner Cessna and the American Eagle, Post's Lockheed, Lacey's Cessna and Lancaster's Great Lakes trainer were here arriving over the fairly dark in the Stinson-Corbin leg. Lacey reported having to land to replace two blown spark plugs. It was the first time

either Lacey or Post had failed to connect to their respective scores their full figure of merit. On the afternoon hop six pilots were late into Greenville, the group including Miss Hanley, Corbin, Decker, Lancaster, Miss Howell and the old reliable Dick Truss. Lancaster and he was expected to land enroute for his. Others reported that the company went had on time, carrying him off his course.

This day's two hops were down before fully left winds, the best flying left being at about 3,000 ft. Al Krugsh, pilot of one of the Statton's, described the water-curtains of his ship upon landing in Greenville. The "squashed" in demonstrating the plane's Hanley Page slats. The damage was repaired, but not in time to permit him to arrive in Augusta, Ga., on scheduled time the next day in time. Others late into Augusta were Herbert Wagner in the Boeing and Wagner in the Travel Air. The Corbin, with the passengers picked up at Winston-Salem, had landed upon the Greenville airport in plenty of time to take off on the appointed route. Earl Statton's Cessna was down into Augusta by Moberg, but in Augusta the ship was taken over by Henry Pondstater, of Raleigh, N. C. For the morning's flight the sky was cloudless with moderate to fresh gusting northeast to east winds at all levels under 7,000 ft.

Due to a series of hard squalls seen by the advance planes between Augusta and Jacksonville the company made, at the suggestion of M. J. Anderson, were again held at a control point until definite assurance of fairly steady conditions enroute was obtained. The air-tripped "Pinecock" Ford, carrying the press, unfortunately had taken off prior to the morning, and slowed through to Jacksonville. The clouds were clearing, but the level showers, at a ceiling of about 4,500 to 5,000 ft., although the mainly, flood hidden miles between Augusta and Jacksonville would make a higher altitude much more desirable for single-engine flight. Many of the pilots questioned this, the weather of the morning, even more than the stretch through the White Mountains.

Although cross winds from east caused the pilots to have to "wait" their places over the course, only one was late into Jacksonville, Nevada. Washine reporting that engine problems. Henry Pondstater, making his first hop, was late on the Tour, but was still ground on the Jacksonville airport and moved his Cessna over, landing a propeller.

HANLEY'S arrival made on the legs of Thursday and Friday were as follows: Richmond-Winston-Salem (143 miles)—Young, 1 hr 9 min 41 sec.; Davis, 1 hr 18 min 33 sec.; Statton, 1 hr 29 min 3 sec. For the first time, Post was not among the first leaders. The performance of Young's Ryan in losing the way and averaging 128 m.p.h. caused general amazement.

Winston-Salem to Greenville (152 miles)—Post, 25 min 18 sec.; Statton, 1 hr 4 min 58 sec.; Hildebrand, 1 hr 5 min 29 sec.; Nagle, 1 hr 6 min 02 sec.; and Wagner, 1 hr 6 min 38 sec. Greenville to Augusta (100 miles)—Lacey, 38 min 11 sec.; Statton, 40 min 01 sec.; Hildebrand, 40 min 39 sec.; Post, 41 min 01 sec.; and Livingston, 41 min 02 sec. Augusta to Jacksonville (210 miles)—Post, 1 hr 15 min 33 sec.; Lacey, 1 hr 20 min 48 sec.; Statton, 1 hr 29 min 12 sec.; Livingston, 1 hr 29 min 32 sec.; and Nagle, 1 hr 30 min 08 sec. On the last three legs the Lockheed averaged 164 m.p.h., while Lacey's Cessna made 156 from Greenville to Jacksonville.

AIRLINES IN THE Canal Zone

By FRANK HAYNES

WHEN Balboa and his merry band of Spanish followers passed out for the first time and behind the city, untroubled waters of the Pacific Ocean, the great mark the end of a journey of less than 30 miles that took nearly two months to complete.

With the advance of sunset the time was eventually cut down to 2 hours by train, and today, the trip is completed in 20 min, an airplane and a regular schedule is maintained.

Early this year, a group of local business men headed by Ralph Sexton, formerly employed by the Panama Canal, but then having a construction company of his own, threatened the initiative and the majority of the capital and forced Balboa Airways, Inc. In the face of strong competition the company secured the consent of the United States government to run planes at a trans-Canal and inter-Canal Canal service. It also secured the consent of the Panamanian government to run a service to connect parts of the country.

The company was incorporated under the laws of Delaware and the \$35,000 that the Canal Zone government requires of all companies operating in the Zone was deposited. It was agreed to use airplanes on the Canal zone because in the event of any trouble the plane could be taken to any part of the Canal as the entire was in over water.

The plane, a seven-passenger Hamilton all-metal airplane powered with a Pratt and Whitney Hornet engine, was the first commercial plane to make a transit of the Canal via the air with a full load of passengers. From May 3 until July 1 a total of 150 trips was made across the Canal without any mishap. Flights released by Mr. Sexton indicated that over 1,400 people traveled in the plane and that nearly 18,000 lb. of freight were carried.

This service across the Canal became as popular that another plane of the same make was ordered and placed in the service on June 10. The service has proved profitable to shipping lines who have used the service to transfer ship's papers and members of the crew across the Canal to avoid entering the locks.

Two all-steel barges have been constructed, one at the Balboa base, and the other on Balboa Island near the Cristobal water harbor. Passengers have perfect facilities for rest and comfort three before embarking or disembarking. It is only a few minutes ride by automobile to the new harbor sections of Panama City and Colon. It has been proved that a person can leave the Canal Central, in the center of Panama City and be in



Headline all metal plane operated daily between Balboa and Colon.

Colon 30 miles across the continent, just 20 miles later.

The first plane across in the morning leaves Balboa at 6:30 am returning, leaves Colon at 8:00. Setting out again from Balboa at 9:30 a.m., it returns in Colon at 1:30 p.m. and arrives back in Balboa a few minutes before the noon train from Colon arrives there. It leaves Balboa again at 4:00 p.m. and returns to Balboa at 5:00 p.m. for the night.

Several night-service trips have been arranged and money spent from the canal boats have traveled the Canal on the morning and then returned over the Canal via air. The trip was away across the Canal is \$10 and the second trip rate is \$15. Special trips by arrangement with the plane traveling slowly for as long as a seven-hour over parts adjacent to the Canal and down the Atlantic and Pacific coasts for a few miles, have been arranged at a cost of \$12.50 per person provided six persons make the trip.

The plane flies at an altitude of approximately 2,000 feet and a clear, bird-eye view can be obtained of the Canal and the wonderful surroundings. It can be more easily appreciated from the air and the operation of the locks and the magnificence of the famous Cristobal Cut can be appreciated better than from a stationary vessel. Employees of the Canal who helped build it have flown over the Canal and maintained as its greatness which interests they had not realized.

An American newspaper printed in Panama City is delivered to its readers across the isthmus on the first plane in the morning and as the service for sale at 7:00 a.m., exactly the hour that its competitors' papers are leaving on the train from Panama. Sales have been reported across the isthmus via plane and 30 min later the goods have been delivered via plane. This speedy service, plus a willingness to oblige at all times, has endeared the operators of the service to residents of Panama and the Canal Zone, and has assured for it a profitable future.



Here appears view of the British rigid airship in her hangar at the Royal Airship Works, Cardington, England.

THE STATE AIRSHIP, R101, is complete at last, after some four years' effort, in which the old airship was mostly devoted to pure research work in wind tunnels and upon the old R33, now broken up, and the last two years given to actual construction. By the time this dispatch appears the ship should have actually flown, but at the time of writing she is waiting complete in the shed for a windproof down, to be manufactured on the new masting tower 200 ft. high at the Royal Airship Works, Cardington, 80 miles from London. [It was not until Oct. 12 that it was not possible to make the first test flight until Friday, Oct. 18.—Ed.]

Before she was due to leave the shed the Air Ministry presented a very full examination of the completed ship and also gave out certain details of weights and expected performance. These add considerably to facts previously made public, and in view of American interest in airship development some of the impressions which followed a careful examination of the ship may also be useful. It is not necessary to describe the general construction of R101 at any great length, as this is common property

by now. However, the main longitudinal girder of R101 is triangular in section with bases of high-tensile steel strip drawn into tube form, by Boulton and Paul of Norwich, with duralumin web and flanges. Duralumin and struts are attached through pin joints. The use of gas-jointing and elimination of an intermediate degree of stiff helps to increase the accuracy of the stress analysis. The main crosswise frames are also of corrugated section and are deep enough to form a rigid ring without any radial bracing, while the gas bags are enclosed in a special form of netting. There is a loss of gas volume by the use of such deep frames, but the designers contend that the whole system makes a much of gas lift to the ship, and avoids all undesirable strains through sagging of the gas or the diffusion of one bag and consequent abnormal pressure conditions within the hull. [The use of duralumin and steel structural members together has been generally avoided in America. Dr. Dornier's flying boats furnish the most visible precedent for employing a composite structure of that kind.—Ed.]

THERE HAS BEEN much criticism from a small but vocal band of opponents of airships at the delay in completing the R101 and the other model; but much of it has been completely ill-informed and it may be said that it has been completely as applied to the airship itself, but has some apparent force when directed to the actual expected performance. So far as can be judged at the moment, when the ship has not flown, there is not a single snag among the many novel features in the design and actual construction of the R101 which justify destructive criticism, but undoubtedly the new Diesel-cycle engines of R101 have not come up to expectations and have seriously affected the performance.

THE BRITISH State Airship R101

By AVIATION'S
British Correspondent

These are eight-cylinder in-line Bensons-Tomada Diesel engines, each cylinder with a bore of 8½ in. and a stroke of 12 in., developing 585-600 hp. per engine. This is about 100 hp. less than was originally expected, and the engines have worked out very much heavier than was originally anticipated, two serious disappointments. The excessive effect of the extra weight in the engines throughout the power nacelles, and of the uselessness in the structure of the ship necessary for carrying this extra distributed load, has meant the addition of an extra 15 tons, and, of course, the passenger load is correspondingly reduced.

Consequently the ship with her present engines is not expected to carry more than 52 passengers instead of the 100 for whom accommodations, on most comfortable lines, have been provided, and the top speed already reduced by the fact that so far no active mental propeller has stood up to the torque of the engines, due in part to the high peak torque load in the Diesel cycle. This means that the variable-pitch propellers, the operating mechanism of which is otherwise satisfactory, cannot be used simply because the Diesel fuel and wooden gearboxes of fixed pitch have had to be substituted. This, in turn, has necessitated one power unit being reserved solely for maneuvering purposes, being fitted with an air-screw for going astern, so only four engines handling 2,420-2,600 hp. are available for forward speed.

Therefore, instead of a designed top speed of 80 m.p.h. the official estimate is now 70 m.p.h. with a cruising speed of 65 m.p.h. and in this event the critics have less cause to make capital out of the failure of the power units, and out of the airship itself, in case it is prevented. But even with the present engines certain notable advantages are being attained. When R101 takes the air she will be the first airship which does not rely upon gasoline. She has discarded that uselessness compromise of hydrogen and white fuel. She is having a fuel oil which costs 825 a ton as against the \$125 needed for gasoline, per ton. [On the C. S. this figure would be about \$20 for gasoline.—Ed.] The fuel, weight for weight, gives 6000 to 30 per cent more range; the engines have become simpler by the elimination of all electrical installations, and, so far as type tests can show, appear to be perfectly reliable while the power is at work they are now used.

Wing-Commander T. E. Cave-Brown-Cave, who is in charge of the machinery installation, is definitely satisfied

Both of the British airships contracted for some five years ago are now nearing readiness for trial. Contrary to the general expectation a year or so ago, the government-designed ship is receiving its first test ahead of that constructed by Commander Murray and the Airship Guarantee Company. The designers of both ships have broken boldly away from past experience and Zeppelin practice, and have introduced a great number of structural innovations, which make their trials of great interest to the whole world. In anticipation of the first flight of the R101, our British correspondent gives a number of details of its design and construction not previously available for publication.

with it. The weight of these Diesels is, I understand, between 4 and 6 lb. per hp., taking only the engine. Wing-Commander Cave-Brown-Cave says that they start up with the chemical case, and more trouble is caused by the small auxiliary gasoline engine used to turn over the big ones for starting.

Perhaps the power eggs or nacelles, had better be exploded in more detail at this point. Each is of cast-iron structure form to reduce head resistance, and contains the main Tomada engine. Linked thereto by a shaft is a Ricardo four-cylinder gasoline engine. This engine is fed by a gasoline tank contained in the power case in a rubber tank. At the first loss of fire, a release handle is pulled, and the whole tank disappears into the blue. This auxiliary engine in two of the fire cases can be chucked into an air compressor, the purpose of which

is to provide pressure to blow fuel or ballast about the ship, the other three engines are coupled to generators to generate current for various purposes, such as lighting, cooking, etc. These generators are also coupled to a constant speed windmill, projecting forward of the car, and at any speed over 40 m.p.h. the windmill takes up the work of generating current and the motors, of course, are stopped.

To start the main engines, Wing Commander Cave-Brown-Cave says, the release raps over the oil injection jets are opened and the engine runs by the gasoline engine with a decompressor valve open until the vent pipe of each jet shows that oil is flowing. Then the cocks are shut, the decompressor closed, and the throttle opened to a considerable extent, when the engine fires straight away. From then on engine speed is controlled much as a locomotive driver controls train speed and is steady. The engine exhausts merely rattle forward one level, the effect of which is to lighten or shorten the actual period during which the pump is injecting oil.

The water cooling represents another novel step, for the evaporative system is used, the only water in circulation being in the jackets. This forms steam and the vapor is led up the side of the ship to a radiator. The steam, then condensed to water, runs back by gravity to a boiler tank, except in the case of one retractable radiator in the bottom of the ship. This serves two engines and it is used to heat the passenger quarters by a process of circulating it into a flow of air being forced by a fan through the various lounges and cabins of the ship. Its efficiency seems proved for with it absent, in when two engines were run in the stand, the temperature in the passenger lounge quickly rose to between 115 and 120 deg. F.

The engine exhausts represent another piece of interesting design, and are really large cylinders about 6 to

9 in. in diameter with the whole of the upper part perforated with holes. Each branch from an exhaust port comes into the cylinder at a tree tangent so that the gases from each engine cylinder start to swirl around the exhaust silencer gradually losing pressure as they swirl just out of the perforated holes. Thus there is little back pressure and the engines are extremely quiet. The whole installation is arranged in the power nacelles so that a mechanic can work on any part of the engine. It is stated that even a complete cylinder could be changed in the air. Each power nacelle is accessible so far as the attachment to the ship is concerned, and the nacelle is not in danger of engines, but complete cars.

The arrangement of the five engines is two attached well forward in frame 4, two in frame 9 and one on the center line at frame 11. This engine is a forward engine so as to secure the utmost control valve from the tail section into the nacelle, the lower halves of which is precisely in line with the propeller, and the reverse engine is the forward port unit. It is stated that every little side pull is done with this offset position, and that it has the advantage of discharging its exhaust in a direction where it causes no disturbance in the even flow of air past the ship.

THERE ARE many most interesting ideas in the machinery installation, such as the system for shifting weight about by air pistons, servo motors for the controls, emergency releases for fuel, and automatic gas valves outside of dealing with a sudden rise at the rate of 45 to 50 m.p.h. It is important to deal with them all in one article, but mention might be made of an electrical indicator in the actual bearing table of the new reactor which tells at once whether the ship is bearing down or pulling up on the nose tip. This directly registers the deflection of the most horizontal tube through which the aerial coupling in the nacelle passes, the degree of deflection being calibrated in tons.

Before proceeding any further the actual dimensions and weight of the ship which is of 5,000,000 cubic feet capacity may be given and for the purposes of comparison they are set against those of the Graf Zeppelin so far as they are known.

	R101	Graf Zeppelin
Length, feet	312	771
Diameter	112	180
Speed, maximum	78 m.p.h.	82 m.p.h.
Speed, cruising	48 m.p.h.	55 m.p.h.
Range with normal payload	5,000 miles	4,120 miles
Normal payload	32 passengers	20 passengers
		25 crew
Total displacement	131 tons	161 tons
Structure, weight without	42 tons	5
Weight of powerplant, engine	21 tons	1
Engine, number	5	4
Engine, type	Benzonover 1	Maybach
	175-494 hp	710 hp
	2,400 hp forward	2,250 hp
	900 astern	
Total hp		

It must be remembered in this comparison that the British ship is built to conform to a high factor of safety, and, as Sir Hubert Wilkes said in a recent issue of *Aviation* [Sept. 21—Ed.], whereas the Graf Zeppelin is designed to withstand a vertical gust of 15 m.p.h. only, R101 is intended to cope with one of 45 m.p.h. the worst known condition and only likely to be met with in the tropics.

The first impression of the ship as entering the huge shed at Cardington is the perfect smoothness of the silver skin, and this is, in part, due to the system of



The main lounge showing the windows and glass partition side of the ship.

tightening girders previously bent longitudinally which can be screwed out to give any desired degree of tension and to ensure that the envelope is always at its best aerodynamic efficiency. Thus at various points along the main frames the envelope can breathe very much on the lines of the gills of a fish. Forward by the nose there is a rug of latex which can only about air to ensure a free and continuous current throughout the ship to clear away all fumes but also ensure that the pressure inside and outside the envelope remains constant. The gill draft with any excess of internal pressure forces swift changes of altitude. Thus to ensure that the skin is always tight to the algorithm of the power cars a small pump in each main nacelle being the propeller shaft, that naturally is constantly moving air at pressure and feeds it into a sort of double skin over the necessary area. Thus the envelope in this region is always tight, regardless of the tightening girders, and friction is prevented.

A WATER RESISTANCE may be made to the passenger accommodation, which approaches the point of luxury with a large lounge stretching right across the ship on the lower portions of bays 6-7 and 7-8 with verandas as wide as the wings and a conspicuous view of the outside world is obtained through safety glass panels in the sides of the ship. The lounge is attractively furnished with easy chairs and sofas for 300 people and on the same deck is a dining room, also lighted from large panels in the side of the ship, that accommodates 50 people. Under this, on the lower deck, is an electric kitchen with

a steel elevator to the dining room above, and on the lower deck also is a smoking room that accommodates about 30 persons. It is a most acceptable addition to the convenience of airship travel. This has the most thoroughly floor to the rest of the ship but it is covered in metal while the walls are fireproofed. There is forced ventilation here and the section, the kitchen, and the wireless room are devoted entirely from the ventilation of the rest of the passenger quarters, and are continually fed with a stream of fresh air, whereas in the other portion fresh air is merely added to that already in circulation. There are two lavatory banks, and the washing accommodation is grouped so as to keep the water used under control and to save weight on jettison and in other directions.

The total area of the upper deck, exclusive of the promenade, is 3,520 sq ft, and that of the lower deck 1,730 sq ft with ability to be extended to 4,000 sq ft, if necessary. The entire passenger accommodation is so designed that there are no localized stresses on the frames or girders. The average weight of the girder work for these decks works out at 1.2 lb. per sq ft, and the covering, principally heavy three-ply strengthened below with ribbing of spindled spruce, is 0.6 lb. per sq ft, and on the open portions of the deck is made to withstand a uniform dead loading of 170 lb. per sq ft.

The bare truss is expected to take from three to six months, after which the initial Empire flight will be made to India with the British Secretary of State for Air, Lord Thomson, as the passenger of honor.



Nose of the great ship R101 on the R101.

PERSONNEL

Col. V. R. Clark and **Col. Thos. Max H. Bane** have been elected to the board of directors of The Aviation Corporation, Colorado. Clark was chief aeronautical engineer for the U. S. Army from 1933 to 1939, serving a number of the National Advisory Committee for Aeronautics in 1936, and is the author of a standard text book on theory of flight. Colonel Bane became chief of the engineering service of the Air Service in 1933 and for the succeeding years was also commanding officer at McClellan Field.

M. R. Niceno, a new district agent in charge of the office of West Coast Air Transport at Seattle, Wash. J. J. Monaghan has resigned. Mr. Nichol is in charge of the Portland office.

John Calverly Wiggins, III, has been appointed private pilot to Gen. Walter Koller.

R. K. Kallala has been appointed purchasing agent for Spartan Aircraft Company, Tulsa, Okla.

C. R. Wynn formerly with Delta Aviation School, has been appointed chief manager for Delta Air Lines, Inc., Love Field, Dallas, Tex.

L. H. Lacey is in operations manager of the new Clinton Airport, Dallas, Tex.

M. A. Swift has resigned from the Midwest Division of Mid-Continent Airlines to become chief engineer of popular activities of Bruckner Aeronautics Corporation, Dayton, Ohio.

Reginald Buchanan, production manager, has been named temporary general manager of Alliance Aircraft Corporation, Albany, Ohio, to succeed the late Andrew W. Hess.

John Deane has been installed for a third term as president of the Atlanta chapter of National Aeronautics Association.

B. D. Adams formerly sales and advertising manager of Apex Aircraft Corporation, has been appointed advertising manager of Detroit Aeronautics Corporation.

H. S. Tiffany is now director of Inter-States Airlines' school at Sky Harbor, Minneapolis, Tenn. **F. P. Francis** has been appointed sales manager for the Tennessee Division of Inter-States Airlines, Inc.

Art Mills formerly with Curtiss Flying Service, Oklahoma City has been named chief instructor for Gliford School of Aviation, Lindbergh Field, San Diego, Calif.

Curt John H. McCutcheon has been named in charge of the Curtiss Flying Service at St. Louis, Mo.

John Van Den Linde, who was associated with the purchasing of the Spirit of St. Louis, has been named as new chief instructor at Airgrad School of Aviation, Lindbergh Field, San Diego, Calif.

Albert Ralph W. Shaker director chief test pilot of the Bunting Airways

of Detroit, will be sales representative of the Spartan Aircraft Company for Michigan, Indiana, Ohio, and Western Pennsylvania—C. L. Hickey, formerly with Aeronautical Consultants, Inc. of Los Angeles on the Pacific Coast, David Packer, for Minnesota, Wisconsin, Illinois, and parts of Iowa.

Dr. Caldwell has joined the first staff of Great Aerials Company, Wichita, Kan.

Robert S. Mayhew, Jr., is new Montreal district manager for Canadian Colonial Airways.

J. W. C. Sullivan has been elected general manager of Westcott Airlines, Ltd., London, England.

John Pratt has been appointed assistant manager at the Akron (Ohio) Municipal Airport.

Royal McKee has been elected general and general manager of Kani Kani Aircraft Company, Sioux City, Iowa. **Maxim G. Gerasim** is new sales manager. **Dr. R. H. Sweeney**, serving president will retain his interest in the corporation.

E. F. Meier has been appointed manager of industrial sales for The Great Corporation, Rockford, Ill., manufacturer of special aircraft.

Miss Zella Kattis has been appointed chief retail representative of Universal Aviation Corporation of St. Louis. **Leo Kerton**, formerly Kani Kani, transferred to the same position at Cleveland as aviation sales manager of the St. Louis office.

J. F. Ferguson has been promoted to assistant chief manager at Central Air Lines division of Central Air Lines, with headquarters at Wichita, Kan.

Walter H. Davis has been appointed production manager at Black (Oregon) Company's plant at Los Angeles Metropolitan Airport.

Arthur Leake has been appointed operations manager for the Curtiss Flying Service Airport at Raleigh, N. C. **Alvin A. Blum**, who has been appointed chief pilot for Sullivan Aircraft Company, Wichita, Kan.

Representatives Named

Burtice NED—Daguer, Airways, Inc., Distribution Co., Chicago, Ill. **Walter A. Wynn**—North and South Dakota, Wisconsin.

R. G. Sparks—Pittsburgh-Great Western Air Corporation, St. Paul, Minn. **Dr. R. H. Sweeney**—North and South Dakota, Wisconsin.

Calverly—Northwest Indiana Flying Service, Goshen, Ind.

Sheridan—C. T. Edwards, Oakland, Calif. for California, Nevada and Oregon.

Texas Air—Stewart, Ltd., Toronto, Ont., for Ontario.

Wynn—New York Aircraft Distribution the territory extended to include northern New Jersey.

Schools & Colleges

MASSACHUSETTS INSTITUTE OF TECHNOLOGY, Boston, Mass., is offering five specialty entrance classes to aviation students at Massachusetts Institute of Tech. This is the beginning of a three-year aeronautical instruction program arranged by the division of university extensions of the Massachusetts Department of Education in co-operation with Paul Daniel C. Byrne of the Institute of Technology.

CURTIS-WHITNEY FLYING SERVICE will open a school at Lawrence, Kan. **INTERSTATE AIRLINES, Inc.** opened a school at Tennessee Sky Harbor, Murfreesboro, Tenn.

ARKANSAS MUNICIPAL AIRPORT will have a flight school institute as a result of a \$100,000 bond issue recently voted by the Alton (Ohr.) Council.

UNIVERSITY OF WASHINGTON, Seattle, will open a school of aviation next fall when the \$250,000 building, given by the Daniel Guggenheim Fund, is completed.

St. James Air College has been opened at St. James, Mo. by G. A. Smith, president, and a bill of \$100,000 and \$100,000, Louis A. A. York, general manager.

SARASOTA UNIVERSITY, SYRACUSE, N. Y., offers a course in aerial photography and surveying. **Carl S. Bush, Jr.** of Seattle, Col. Claude H. Johnson, Sherman, Mo. and Fredrick and Carl E. Lord will serve as an advisory committee to Dean Louis Mottel of the College of Applied Science.

REGENCY AVIATION COLLEGE, 129 W. 42nd St., New York, N. Y., will open Oct. 27 by Rosemary Avonson School.

NATIONAL AIRWAYS, Inc., Detroit, Mich., has opened a training school at Ann Arbor.

UNIVERSITY OF WICHITA (Kan.) Engineering School is completing a new building to be used for experiments in connection with the University course in aviation engineering.

CURTIS-WHITNEY FLYING SERVICE reports a total of \$325 in loans by individuals during September at its five branches, the largest total for any single month this year. A fleet of 343 planes was used in the single month's service.

UNIVERSITY OF SOUTHERN CALIFORNIA has 173 students enrolled in the degree in commercial aviation, airport management, airplane repair, theory of flight, and meteorology and air navigation.

CENTRAL TECHNICAL SCHOOL, Toronto, Ont., cooperating with Toronto Area Club and Technical Aircraft Company has enrolled more than 250 students in an evening course and has been invited to form a unit.

GREAT NORTHERN AVIATION CORPORATION plans to establish a school at the Municipal Airport, Duluth, Minn., in addition to its school at Pike Lake, Superior, Wis.



Moves to Provide More Federal Control

WASHINGTON (A. C.)—Senator William of New Mexico representing the disaster of T. A. G. Co. of San Francisco, has introduced a Senate bill, designed to prevent air crashes. His resolution including this report was held up by Senator Wagoner of Connecticut and other Senators who do not believe that any good purpose would be served by a general certification of the aviation industry. Due to the gravity of aviation losses to expedite passage of the bill had a resolution for such an investigation by Senator Wagoner. Progress cannot be referred to a committee as long as there is objection.

Senator Wagoner has given special attention to this problem and a bill of Oct. 14 providing for complete regulation of operations are under the Senate Commerce Committee. A bill does not have the same fate that a resolution does but may be referred automatically to a committee. This bill will be submitted by the Interstate Commerce Committee of the Senate and committee and executive hearings are arranged. Senator Wagoner is particularly out of sympathy with the Bureau of Commerce policy of refusing to permit complete regulation of air transport.

T. A. G. and other air line member just arrived with rail carriers when they to the Interstate Commerce Commission. Senator Wagoner believes, therefore, that these air carriers should be regulated by the Interstate Commerce Commission. The bill requires the rail carriers which participate with them in the joint haul. Senator Wagoner's bill is now under the committee.

It means aviation provides that the Commission shall exercise its jurisdiction through the issuance of certificates of public convenience and necessity and that rates and schedules shall also be regulated. The bill further provides that no person shall be liable for personal injury or death as caused by any such rail carrier. Maximum liability of injury compensation in railroad cases is \$10,000.

The general attitude of the aviation industry toward the issue of Interstate Commerce Commission supervision is characterized by intense opposition.

Arkansas Adds Airport Project

LITTLE ROCK (Ark.)—The help of state highway department, authority and the advice of the state highway commissioner are available to the committee at this time in preparation of report construction committee to a bill passed by the legislature. Transportation is something a great deal.

Open Portland Radio Link

PORTLAND (Ore.)—Radio communication between plane and ground was inaugurated last month when the \$25,000 government radio survey communication station at Fisher Road was placed in operation. The station is in charge of W. E. Cullum, acting chief. This is the first station now in operation on the Coast.

Plan Southwestern Mail Route Discussion

WASHINGTON (A. C.)—A hearing on the new transcontinental mail route, transcontinental air mail line has been announced by Assistant Postmaster General W. Irving Glover for Nov. 25 at 10 a. m. in the conference room of the Post Office Department. The Interstate Commerce Commission on aviation holding the hearing would be for first-hand information from all interested parties, and is opening the hearing to all those desiring a say in the matter.

One route suggested runs from St. Louis via Tulsa, Fort Worth and Dallas to Los Angeles. Another suggestion is for the extension of the existing Alaska-Birmingham line to Fort Worth and Denver and thence to Los Angeles. A third proposal contemplates a more southern route, linking New Orleans, Houston, San Antonio, El Paso, San Diego and Los Angeles. Southern Air Transport has already an existing route, or have contracted to do so, along the latter of the proposed routes. Their present line running Atlanta-Birmingham-New Orleans and New Orleans-Denver-Portland.

Committee will meet on the present day 1.



Airports and Airlines

Open Portland Radio Link

PORTLAND (Ore.)—Radio communication between plane and ground was inaugurated last month when the \$25,000 government radio survey communication station at Fisher Road was placed in operation. The station is in charge of W. E. Cullum, acting chief. This is the first station now in operation on the Coast.

Plan Southwestern Mail Route Discussion

WASHINGTON (A. C.)—A hearing on the new transcontinental mail route, transcontinental air mail line has been announced by Assistant Postmaster General W. Irving Glover for Nov. 25 at 10 a. m. in the conference room of the Post Office Department. The Interstate Commerce Commission on aviation holding the hearing would be for first-hand information from all interested parties, and is opening the hearing to all those desiring a say in the matter.

One route suggested runs from St. Louis via Tulsa, Fort Worth and Dallas to Los Angeles. Another suggestion is for the extension of the existing Alaska-Birmingham line to Fort Worth and Denver and thence to Los Angeles. A third proposal contemplates a more southern route, linking New Orleans, Houston, San Antonio, El Paso, San Diego and Los Angeles. Southern Air Transport has already an existing route, or have contracted to do so, along the latter of the proposed routes. Their present line running Atlanta-Birmingham-New Orleans and New Orleans-Denver-Portland.

Committee will meet on the present day 1.

Push Plans for Bog Island Port

FAIRHAVEN, N. Y.—Specially set toward the corporation and development of Bog Island is a municipality. The city has been planning the development of Bog Island as a municipality. The city has been planning the development of Bog Island as a municipality. The city has been planning the development of Bog Island as a municipality.

Arkansas Adds Airport Project

LITTLE ROCK (Ark.)—The help of state highway department, authority and the advice of the state highway commissioner are available to the committee at this time in preparation of report construction committee to a bill passed by the legislature. Transportation is something a great deal.

Open Portland Radio Link

PORTLAND (Ore.)—Radio communication between plane and ground was inaugurated last month when the \$25,000 government radio survey communication station at Fisher Road was placed in operation. The station is in charge of W. E. Cullum, acting chief. This is the first station now in operation on the Coast.

Plan Southwestern Mail Route Discussion

WASHINGTON (A. C.)—A hearing on the new transcontinental mail route, transcontinental air mail line has been announced by Assistant Postmaster General W. Irving Glover for Nov. 25 at 10 a. m. in the conference room of the Post Office Department. The Interstate Commerce Commission on aviation holding the hearing would be for first-hand information from all interested parties, and is opening the hearing to all those desiring a say in the matter.



Mail Problem Puzzles Conferees

Kelly Recommends That Short Routes Be Extended

WASHINGTON (A. C.)—Conferees between Post Office Department officials and representatives of air mail contract routes were adjourned from Oct. 18 to Oct. 26, due to continued failure to agree on a satisfactory formula. It was reported that after the conferees have submitted their inability to agree on a suitable "yardstick," was not satisfactory proposed by the Post Office Department, but strenuous objections to it were made by the Office officials as well as by the two airlines and others in such an attempt to reach a compromise.

In addition to the problem of determining the relative importance of flying routes of night and day flying, length and terms of routes, and differences in types of planes used other "variables" are being taken into consideration which are being kept under the present. They are said to include such points as wind and weather conditions and wages for pilots.

Individual Conferees Encouraged

Hope for an early solution is seen, however, in the fact that the Interstate Commerce Commission on aviation holding the hearing would be for first-hand information from all interested parties, and is opening the hearing to all those desiring a say in the matter.

Arkansas Adds Airport Project

LITTLE ROCK (Ark.)—The help of state highway department, authority and the advice of the state highway commissioner are available to the committee at this time in preparation of report construction committee to a bill passed by the legislature. Transportation is something a great deal.

Open Portland Radio Link

PORTLAND (Ore.)—Radio communication between plane and ground was inaugurated last month when the \$25,000 government radio survey communication station at Fisher Road was placed in operation. The station is in charge of W. E. Cullum, acting chief. This is the first station now in operation on the Coast.

Plan Southwestern Mail Route Discussion

WASHINGTON (A. C.)—A hearing on the new transcontinental mail route, transcontinental air mail line has been announced by Assistant Postmaster General W. Irving Glover for Nov. 25 at 10 a. m. in the conference room of the Post Office Department. The Interstate Commerce Commission on aviation holding the hearing would be for first-hand information from all interested parties, and is opening the hearing to all those desiring a say in the matter.

Arkansas Adds Airport Project

LITTLE ROCK (Ark.)—The help of state highway department, authority and the advice of the state highway commissioner are available to the committee at this time in preparation of report construction committee to a bill passed by the legislature. Transportation is something a great deal.

Open Portland Radio Link

Foreign News Briefs

Gold Arzobispo, Buenos Aires, established an official record of 12 min three mile swim in a Foca Wall place with 70 gal. Swimsuit outfit.

Argentina Argentina has begun regular operation of a weekly air mail service between Buenos Aires and Santiago, Chile.

Aerialist committees of leading British universities have formed the nucleus for an aviation league of Lloyd's Register of Shipping.

S.I.S.A. will soon open a new office between Trieste, Venice, Milan, Genoa and Marseille. The Italian League is expected to spend a sum of \$4,000,000 for to be spread over a period of 10 yr.

The Argentine Air Force consists of one French pilot being the only place which has been permitted to enter the country.

Five tons of gold valued at nearly \$2,500,000, were recently carried from London to Paris in one day in Imperial Airways plane. There are now 40 tons of gold now carried across the Channel.

The French company has obtained a contract to carry European mail from London to Paris, to be carried in Imperial Airways planes to Paris, and then to carry mail from Paris to Rome.

Interior equipment, including a smoking room with bar, is being added to the Dornier DO 3, which has made 30 successful flights during the past two months.

Owing to successful results of test flights, regular night air mail service between Brussels and London will be inaugurated and will consist of:

Bayreuth, Mannheim, Munich, Germany, learned to manufacture D-4 Whitney Rocket engines, has completed a 30 hr test of engine on a test of similar design which employs a German type reduction gear with a ratio of 1.5 to 1 to give the normal crankshaft speed of 2700 r.p.m.

Rome Air Force (Aeronautica) is the name of a new French monthly despatch of military aircraft.

The French government has ordered a Lockheed "Sukhoi" patrolplane.

Italian "Sukhoi" patrolplane, have been adapted by the Swiss Air Force.

Air mail and passenger service between El Paso, Tex., and Mexico City via Chihuahua, Tijuana and San Juan was resumed Oct 1 from every third day to daily.

Polish-Latin American Airways has bought land for an airport in Rio de Janeiro, Brazil.

Gray Mark airplanes are to be used for training purposes by the Portuguese Naval Air Force. The Portuguese has adapted a Gray Mark two-seater for its personnel use.

The first "Lancaster" is a six passenger cabin monoplane to be fitted with

three "Mongoose" engines, is under construction in the Berlin Aircraft Society Company's plant at Melbourne, Australia.

New reports have been received recently by Australian Aerial Services, Ltd., at Adelaide, Victoria, Melbourne, New South Wales, and Melbourne, New South Wales.

An All-Atlantic Aerial Exhibition now opened in the Exhibition Building, Melbourne, Sept 14.

Weekly aviation service by airplane between Beirut, Syria, and Marseille, with stops at Athens, Greece, and Naples, Italy, was started by a French company. The line has received a local subsidy from the French and Swiss governments.

It is reported that five Italian planes are being prepared for a simultaneous transatlantic flight, with New York as the ultimate objective.

Successful tests of a radio device which indicates direction, distance and characteristics of fog signals have been made in England.

Roth-Kleinmann Works, Germany, are considering plans for establishing a branch factory in China.

The Prussian company has stipulated a license to build the new Junkers Ju-200 engine in France and French colonies.

The Mexican Good Will plane in which Col. Pablo Salas and Lt. Gen. Amador Gomez were making a tour of Latin America was practically demolished when the plane was near Nobel Stadium.

Up to Sept. 2 of this year, 36,365 planes had been received, 36,365 of 1st, 2nd and 3rd class, in a total of 1,371,678 sq. ft. of flying on the Peninsula, 2nd class, 3rd class, 4th class, 5th class, 6th class, 7th class, 8th class, 9th class, 10th class, 11th class, 12th class, 13th class, 14th class, 15th class, 16th class, 17th class, 18th class, 19th class, 20th class, 21st class, 22nd class, 23rd class, 24th class, 25th class, 26th class, 27th class, 28th class, 29th class, 30th class, 31st class, 32nd class, 33rd class, 34th class, 35th class, 36th class, 37th class, 38th class, 39th class, 40th class, 41st class, 42nd class, 43rd class, 44th class, 45th class, 46th class, 47th class, 48th class, 49th class, 50th class, 51st class, 52nd class, 53rd class, 54th class, 55th class, 56th class, 57th class, 58th class, 59th class, 60th class, 61st class, 62nd class, 63rd class, 64th class, 65th class, 66th class, 67th class, 68th class, 69th class, 70th class, 71st class, 72nd class, 73rd class, 74th class, 75th class, 76th class, 77th class, 78th class, 79th class, 80th class, 81st class, 82nd class, 83rd class, 84th class, 85th class, 86th class, 87th class, 88th class, 89th class, 90th class, 91st class, 92nd class, 93rd class, 94th class, 95th class, 96th class, 97th class, 98th class, 99th class, 100th class, 101st class, 102nd class, 103rd class, 104th class, 105th class, 106th class, 107th class, 108th class, 109th class, 110th class, 111th class, 112th class, 113th class, 114th class, 115th class, 116th class, 117th class, 118th class, 119th class, 120th class, 121st class, 122nd class, 123rd class, 124th class, 125th class, 126th class, 127th class, 128th class, 129th class, 130th class, 131st class, 132nd class, 133rd class, 134th class, 135th class, 136th class, 137th class, 138th class, 139th class, 140th class, 141st class, 142nd class, 143rd class, 144th class, 145th class, 146th class, 147th class, 148th class, 149th class, 150th class, 151st class, 152nd class, 153rd class, 154th class, 155th class, 156th class, 157th class, 158th class, 159th class, 160th class, 161st class, 162nd class, 163rd class, 164th class, 165th class, 166th class, 167th class, 168th class, 169th class, 170th class, 171st class, 172nd class, 173rd class, 174th class, 175th class, 176th class, 177th class, 178th class, 179th class, 180th class, 181st class, 182nd class, 183rd class, 184th class, 185th class, 186th class, 187th class, 188th class, 189th class, 190th class, 191st class, 192nd class, 193rd class, 194th class, 195th class, 196th class, 197th class, 198th class, 199th class, 200th class, 201st class, 202nd class, 203rd class, 204th class, 205th class, 206th class, 207th class, 208th class, 209th class, 210th class, 211th class, 212th class, 213th class, 214th class, 215th class, 216th class, 217th class, 218th class, 219th class, 220th class, 221st class, 222nd class, 223rd class, 224th class, 225th class, 226th class, 227th class, 228th class, 229th class, 230th class, 231st class, 232nd class, 233rd class, 234th class, 235th class, 236th class, 237th class, 238th class, 239th class, 240th class, 241st class, 242nd class, 243rd class, 244th class, 245th class, 246th class, 247th class, 248th class, 249th class, 250th class, 251st class, 252nd class, 253rd class, 254th class, 255th class, 256th class, 257th class, 258th class, 259th class, 260th class, 261st class, 262nd class, 263rd class, 264th class, 265th class, 266th class, 267th class, 268th class, 269th class, 270th class, 271st class, 272nd class, 273rd class, 274th class, 275th class, 276th class, 277th class, 278th class, 279th class, 280th class, 281st class, 282nd class, 283rd class, 284th class, 285th class, 286th class, 287th class, 288th class, 289th class, 290th class, 291st class, 292nd class, 293rd class, 294th class, 295th class, 296th class, 297th class, 298th class, 299th class, 300th class, 301st class, 302nd class, 303rd class, 304th class, 305th class, 306th class, 307th class, 308th class, 309th class, 310th class, 311th class, 312th class, 313th class, 314th class, 315th class, 316th class, 317th class, 318th class, 319th class, 320th class, 321st class, 322nd class, 323rd class, 324th class, 325th class, 326th class, 327th class, 328th class, 329th class, 330th class, 331st class, 332nd class, 333rd class, 334th class, 335th class, 336th class, 337th class, 338th class, 339th class, 340th class, 341st class, 342nd class, 343rd class, 344th class, 345th class, 346th class, 347th class, 348th class, 349th class, 350th class, 351st class, 352nd class, 353rd class, 354th class, 355th class, 356th class, 357th class, 358th class, 359th class, 360th class, 361st class, 362nd class, 363rd class, 364th class, 365th class, 366th class, 367th class, 368th class, 369th class, 370th class, 371st class, 372nd class, 373rd class, 374th class, 375th class, 376th class, 377th class, 378th class, 379th class, 380th class, 381st class, 382nd class, 383rd class, 384th class, 385th class, 386th class, 387th class, 388th class, 389th class, 390th class, 391st class, 392nd class, 393rd class, 394th class, 395th class, 396th class, 397th class, 398th class, 399th class, 400th class, 401st class, 402nd class, 403rd class, 404th class, 405th class, 406th class, 407th class, 408th class, 409th class, 410th class, 411th class, 412th class, 413th class, 414th class, 415th class, 416th class, 417th class, 418th class, 419th class, 420th class, 421st class, 422nd class, 423rd class, 424th class, 425th class, 426th class, 427th class, 428th class, 429th class, 430th class, 431st class, 432nd class, 433rd class, 434th class, 435th class, 436th class, 437th class, 438th class, 439th class, 440th class, 441st class, 442nd class, 443rd class, 444th class, 445th class, 446th class, 447th class, 448th class, 449th class, 450th class, 451st class, 452nd class, 453rd class, 454th class, 455th class, 456th class, 457th class, 458th class, 459th class, 460th class, 461st class, 462nd class, 463rd class, 464th class, 465th class, 466th class, 467th class, 468th class, 469th class, 470th class, 471st class, 472nd class, 473rd class, 474th class, 475th class, 476th class, 477th class, 478th class, 479th class, 480th class, 481st class, 482nd class, 483rd class, 484th class, 485th class, 486th class, 487th class, 488th class, 489th class, 490th class, 491st class, 492nd class, 493rd class, 494th class, 495th class, 496th class, 497th class, 498th class, 499th class, 500th class, 501st class, 502nd class, 503rd class, 504th class, 505th class, 506th class, 507th class, 508th class, 509th class, 510th class, 511th class, 512th class, 513th class, 514th class, 515th class, 516th class, 517th class, 518th class, 519th class, 520th class, 521st class, 522nd class, 523rd class, 524th class, 525th class, 526th class, 527th class, 528th class, 529th class, 530th class, 531st class, 532nd class, 533rd class, 534th class, 535th class, 536th class, 537th class, 538th class, 539th class, 540th class, 541st class, 542nd class, 543rd class, 544th class, 545th class, 546th class, 547th class, 548th class, 549th class, 550th class, 551st class, 552nd class, 553rd class, 554th class, 555th class, 556th class, 557th class, 558th class, 559th class, 560th class, 561st class, 562nd class, 563rd class, 564th class, 565th class, 566th class, 567th class, 568th class, 569th class, 570th class, 571st class, 572nd class, 573rd class, 574th class, 575th class, 576th class, 577th class, 578th class, 579th class, 580th class, 581st class, 582nd class, 583rd class, 584th class, 585th class, 586th class, 587th class, 588th class, 589th class, 590th class, 591st class, 592nd class, 593rd class, 594th class, 595th class, 596th class, 597th class, 598th class, 599th class, 600th class, 601st class, 602nd class, 603rd class, 604th class, 605th class, 606th class, 607th class, 608th class, 609th class, 610th class, 611th class, 612th class, 613th class, 614th class, 615th class, 616th class, 617th class, 618th class, 619th class, 620th class, 621st class, 622nd class, 623rd class, 624th class, 625th class, 626th class, 627th class, 628th class, 629th class, 630th class, 631st class, 632nd class, 633rd class, 634th class, 635th class, 636th class, 637th class, 638th class, 639th class, 640th class, 641st class, 642nd class, 643rd class, 644th class, 645th class, 646th class, 647th class, 648th class, 649th class, 650th class, 651st class, 652nd class, 653rd class, 654th class, 655th class, 656th class, 657th class, 658th class, 659th class, 660th class, 661st class, 662nd class, 663rd class, 664th class, 665th class, 666th class, 667th class, 668th class, 669th class, 670th class, 671st class, 672nd class, 673rd class, 674th class, 675th class, 676th class, 677th class, 678th class, 679th class, 680th class, 681st class, 682nd class, 683rd class, 684th class, 685th class, 686th class, 687th class, 688th class, 689th class, 690th class, 691st class, 692nd class, 693rd class, 694th class, 695th class, 696th class, 697th class, 698th class, 699th class, 700th class, 701st class, 702nd class, 703rd class, 704th class, 705th class, 706th class, 707th class, 708th class, 709th class, 710th class, 711th class, 712th class, 713th class, 714th class, 715th class, 716th class, 717th class, 718th class, 719th class, 720th class, 721st class, 722nd class, 723rd class, 724th class, 725th class, 726th class, 727th class, 728th class, 729th class, 730th class, 731st class, 732nd class, 733rd class, 734th class, 735th class, 736th class, 737th class, 738th class, 739th class, 740th class, 741st class, 742nd class, 743rd class, 744th class, 745th class, 746th class, 747th class, 748th class, 749th class, 750th class, 751st class, 752nd class, 753rd class, 754th class, 755th class, 756th class, 757th class, 758th class, 759th class, 760th class, 761st class, 762nd class, 763rd class, 764th class, 765th class, 766th class, 767th class, 768th class, 769th class, 770th class, 771st class, 772nd class, 773rd class, 774th class, 775th class, 776th class, 777th class, 778th class, 779th class, 780th class, 781st class, 782nd class, 783rd class, 784th class, 785th class, 786th class, 787th class, 788th class, 789th class, 790th class, 791st class, 792nd class, 793rd class, 794th class, 795th class, 796th class, 797th class, 798th class, 799th class, 800th class, 801st class, 802nd class, 803rd class, 804th class, 805th class, 806th class, 807th class, 808th class, 809th class, 810th class, 811th class, 812th class, 813th class, 814th class, 815th class, 816th class, 817th class, 818th class, 819th class, 820th class, 821st class, 822nd class, 823rd class, 824th class, 825th class, 826th class, 827th class, 828th class, 829th class, 830th class, 831st class, 832nd class, 833rd class, 834th class, 835th class, 836th class, 837th class, 838th class, 839th class, 840th class, 841st class, 842nd class, 843rd class, 844th class, 845th class, 846th class, 847th class, 848th class, 849th class, 850th class, 851st class, 852nd class, 853rd class, 854th class, 855th class, 856th class, 857th class, 858th class, 859th class, 860th class, 861st class, 862nd class, 863rd class, 864th class, 865th class, 866th class, 867th class, 868th class, 869th class, 870th class, 871st class, 872nd class, 873rd class, 874th class, 875th class, 876th class, 877th class, 878th class, 879th class, 880th class, 881st class, 882nd class, 883rd class, 884th class, 885th class, 886th class, 887th class, 888th class, 889th class, 890th class, 891st class, 892nd class, 893rd class, 894th class, 895th class, 896th class, 897th class, 898th class, 899th class, 900th class, 901st class, 902nd class, 903rd class, 904th class, 905th class, 906th class, 907th class, 908th class, 909th class, 910th class, 911th class, 912th class, 913th class, 914th class, 915th class, 916th class, 917th class, 918th class, 919th class, 920th class, 921st class, 922nd class, 923rd class, 924th class, 925th class, 926th class, 927th class, 928th class, 929th class, 930th class, 931st class, 932nd class, 933rd class, 934th class, 935th class, 936th class, 937th class, 938th class, 939th class, 940th class, 941st class, 942nd class, 943rd class, 944th class, 945th class, 946th class, 947th class, 948th class, 949th class, 950th class, 951st class, 952nd class, 953rd class, 954th class, 955th class, 956th class, 957th class, 958th class, 959th class, 960th class, 961st class, 962nd class, 963rd class, 964th class, 965th class, 966th class, 967th class, 968th class, 969th class, 970th class, 971st class, 972nd class, 973rd class, 974th class, 975th class, 976th class, 977th class, 978th class, 979th class, 980th class, 981st class, 982nd class, 983rd class, 984th class, 985th class, 986th class, 987th class, 988th class, 989th class, 990th class, 991st class, 992nd class, 993rd class, 994th class, 995th class, 996th class, 997th class, 998th class, 999th class, 1000th class, 1001st class, 1002nd class, 1003rd class, 1004th class, 1005th class, 1006th class, 1007th class, 1008th class, 1009th class, 1010th class, 1011th class, 1012th class, 1013th class, 1014th class, 1015th class, 1016th class, 1017th class, 1018th class, 1019th class, 1020th class, 1021st class, 1022nd class, 1023rd class, 1024th class, 1025th class, 1026th class, 1027th class, 1028th class, 1029th class, 1030th class, 1031st class, 1032nd class, 1033rd class, 1034th class, 1035th class, 1036th class, 1037th class, 1038th class, 1039th class, 1040th class, 1041st class, 1042nd class, 1043rd class, 1044th class, 1045th class, 1046th class, 1047th class, 1048th class, 1049th class, 1050th class, 1051st class, 1052nd class, 1053rd class, 1054th class, 1055th class, 1056th class, 1057th class, 1058th class, 1059th class, 1060th class, 1061st class, 1062nd class, 1063rd class, 1064th class, 1065th class, 1066th class, 1067th class, 1068th class, 1069th class, 1070th class, 1071st class, 1072nd class, 1073rd class, 1074th class, 1075th class, 1076th class, 1077th class, 1078th class, 1079th class, 1080th class, 1081st class, 1082nd class, 1083rd class, 1084th class, 1085th class, 1086th class, 1087th class, 1088th class, 1089th class, 1090th class, 1091st class, 1092nd class, 1093rd class, 1094th class, 1095th class, 1096th class, 1097th class, 1098th class, 1099th class, 1100th class, 1101st class, 1102nd class, 1103rd class, 1104th class, 1105th class, 1106th class, 1107th class, 1108th class, 1109th class, 1110th class, 1111th class, 1112th class, 1113th class, 1114th class, 1115th class, 1116th class, 1117th class, 1118th class, 1119th class, 1120th class, 1121st class, 1122nd class, 1123rd class, 1124th class, 1125th class, 1126th class, 1127th class, 1128th class, 1129th class, 1130th class, 1131st class, 1132nd class, 1133rd class, 1134th class, 1135th class, 1136th class, 1137th class, 1138th class, 1139th class, 1140th class, 1141st class, 1142nd class, 1143rd class, 1144th class, 1145th class, 1146th class, 1147th class, 1148th class, 1149th class, 1150th class, 1151st class, 1152nd class, 1153rd class, 1154th class, 1155th class, 1156th class, 1157th class, 1158th class, 1159th class, 1160th class, 1161st class, 1162nd class, 1163rd class, 1164th class, 1165th class, 1166th class, 1167th class, 1168th class, 1169th class, 1170th class, 1171st class, 1172nd class, 1173rd class, 1174th class, 1175th class, 1176th class, 1177th class, 1178th class, 1179th class, 1180th class, 1181st class, 1182nd class, 1183rd class, 1184th class, 1185th class, 1186th class, 1187th class, 1188th class, 1189th class, 1190th class, 1191st class, 1192nd class, 1193rd class, 1194th class, 1195th class, 1196th class, 1197th class, 1198th class, 1199th class, 1200th class, 1201st class, 1202nd class, 1203rd class, 1204th class, 1205th class, 1206th class, 1207th class, 1208th class, 1209th class, 1210th class, 1211th class, 1212th class, 1213th class, 1214th class, 1215th class, 1216th class, 1217th class, 1218th class, 1219th class, 1220th class, 1221st class, 1222nd class, 1223rd class, 1224th class, 1225th class, 1226th class, 1227th class, 1228th class, 1229th class, 1230th class, 1231st class, 1232nd class, 1233rd class, 1234th class, 1235th class, 1236th class, 1237th class, 1238th class, 1239th class, 1240th class, 1241st class, 1242nd class, 1243rd class, 1244th class, 1245th class, 1246th class, 1247th class, 1248th class, 1249th class, 1250th class, 1251st class, 1252nd class, 1253rd class, 1254th class, 1255th class, 1256th class, 1257th class, 1258th class, 1259th class, 1260th class, 1261st class, 1262nd class, 1263rd class, 1264th class, 1265th class, 1266th class, 1267th class, 1268th class, 1269th class, 1270th class, 1271st class, 1272nd class, 1273rd class, 1274th class, 1275th class, 1276th class, 1277th class, 1278th class, 1279th class, 1280th class, 1281st class, 1282nd class, 1283rd class, 1284th class, 1285th class, 1286th class, 1287th class, 1288th class, 1289th class, 1290th class, 1291st class, 1292nd class, 1293rd class, 1294th class, 1295th class, 1296th class, 1297th class, 1298th class, 1299th class, 1300th class, 1301st class, 1302nd class, 1303rd class, 1304th class, 1305th class, 1306th class, 1307th class, 1308th class, 1309th class, 1310th class, 1311th class, 1312th class, 1313th class, 1314th class, 1315th class, 1316th class, 1317th class, 1318th class, 1319th class, 1320th class, 1321st class, 1322nd class, 1323rd class, 1324th class, 1325th class, 1326th class, 1327th class, 1328th class, 1329th class, 1330th class, 1331st class, 1332nd class, 1333rd class, 1334th class, 1335th class, 1336th class, 1337th class, 1338th class, 1339th class, 1340th class, 1341st class, 1342nd class, 1343rd class, 1344th class, 1345th class, 1346th class, 1347th class, 1348th class, 1349th class, 1350th class, 1351st class, 1352nd class, 1353rd class, 1354th class, 1355th class, 1356th class, 1357th class, 1358th class, 1359th class, 1360th class, 1361st class, 1362nd class, 1363rd class, 1364th class, 1365th class, 1366th class, 1367th class, 1368th class, 1369th class, 1370th class, 1371st class, 1372nd class, 1373rd class, 1374th class, 1375th class, 1376th class, 1377th class, 1378th class, 1379th class, 1380th class, 1381st class, 1382nd class, 1383rd class, 1384th class, 1385th class, 1386th class, 1387th class, 1388th class, 1389th class, 1390th class, 1391st class, 1392nd class, 1393rd class, 1394th class, 1395th class, 1396th class, 1397th class, 1398th class, 1399th class, 1400th class, 1401st class, 1402nd class, 1403rd class, 1404th class, 1405th class, 1406th class, 1407th class, 1408th class, 1409th class, 1410th class, 1411th class, 1412th class, 1413th class, 1414th class, 1415th class, 1416th class, 1417th class, 1418th class, 1419th class, 1420th class, 1421st class, 1422nd class, 1423rd class, 1424th class, 1425th class, 1426th class, 1427th class, 1428th class, 1429th class, 1430th class, 1431st class, 1432nd class, 1433rd class, 1434th class, 1435th class, 1436th class, 1437th class, 1438th class, 1439th class



3:38 P.M. . . . A perfect Seaplane takes off.

Gun the "Wasp" engines as a Sikorsky Amphibian and an unusually short run picks her off the water. Ease back on the comfortable control wheel and her fast, easy climb cannot but stir your honest admiration. A gentleman's ship if ever there was one!

To state it even more definitely: A ship for men who know and love the water.

And yet you may want to land a dozen miles from water. Reach for that convenient landing gear control and in less than fifty seconds . . .



3:38:50 P.M. . and the Sikorsky "S-38" is an ideal land plane

The wheels slide down, moved by smooth, positive hydraulic control . . . and you have a ship completely at home under land conditions. The "S-38" is now equipped with Sikorsky designed brakes which bring her to a stop in less than 300 feet.

It is natural to think of the Sikorsky Amphibian as a ship of comfort and luxury . . . but it is interesting to be more specific. She has a ceiling, for example, of 18,000 feet, a cruising speed of 110 and a high speed of more than 125 miles an hour. She will fly . . . and maneuver . . . on either engine.

SIKORSKY AVIATION CORPORATION

DIVISION OF UNITED AIRCRAFT
& TRANSPORT CORPORATION
Bridgeport, Connecticut



Taking its Place IN THE SKY...

"A-W-G" Armor-Lite has earned its place in the sky by right of superior service.

"A-W-G" Armor-Lite scatter-proof glass is a laminated glass of exceptionally high quality. It provides positive protection against the hazard of flying glass.

For all aircraft, specify "A-W-G" Armor-Lite, Scatter-Proof, Laminated Glass. It is available in a wide range of sizes, thicknesses and weights, from heavy Bullet-Proof for banks to Featherweight designed especially for the aviation industry . . . Write for booklet . . . Address . . .

ARMOR-LITE
A-W-G CO.

The following shows where it is used in the construction of all types of aircraft: "A-W-G" Armor-Lite. Look for it. It is your protection against vibration.

AMERICAN WINDOW GLASS CO.

World's Largest Producer of Window Glass
PITTSBURGH, PA.

BETTER PILOTS from Diversified Training

The AIRTECH Fleet

includes five distinct

types of America's

Foremost

Aircraft

Realizing that experience is the best teacher, the complete AIRTECH System provides diversified training in five distinct types of modern aircraft.

In mastering these open ships and large and small cabin planes, AIRTECH students gain the ability to pilot any of the aircraft, predominant in modern air commerce.

This essential training, in a Department of Commerce approved Ground and Flying School, builds the foundation for your success in aviation.

Airtech School of Aviation

Department of Commerce Approved
Transport Ground and Flying School

Lindbergh Field

San Diego, California



*For the second
successive year...* **WACO**



The two WACO entries, piloted by John Livingston and Arthur J. Berle, ran neck-and-neck throughout the tour, finishing with scores far ahead of the other 27 contestants. Last year, also, WACO led the field.



MODERATE PRICES AND CONVENIENT TERMS MAKE IT EASY TO OWN A WACO. COMPLETE DETAILS AT YOUR REQUEST

WINS THE NATIONAL AIR TOUR

Repeating its spectacular performance of last year, and scoring a still more impressive victory, WACO again won by a comfortable margin.

The rules of the competition for the Edsel Ford trophy are such that, by deliberate intent, the practical performance of an airplane is given definite valuation. The record of the two WACOs is, therefore, conclusive proof of WACO's outstanding merit . . . of WACO's rating as the practical airplane to own and to fly.

The Fifth National Air Tour again confirms the superior performance which has made WACO the most popular commercial aircraft in America.

THE WACO AIRPLANE COMPANY, TROY, OHIO

AND, IF YOU WISH, ANY ONE OF THE NEARLY 300 WACO DEALERS WILL ARRANGE A FLIGHT DEMONSTRATION FOR YOU

RECOGNITION

RYAN
WACO
EMSCO
LAIRD
MARTIN
FOKKER
BREESE
FERNIG
LUGLIN
LOENING
SPARTAN
GENERAL
SWALLOW
STEARMAN
HAMILTON
PITCAIRN
FLAMINGO
BELLANCA
SIKORSKY
TRAVEL AIR
GREAT LAKES
BERLINER-JOYCE
CUNNINGHAM-HALL

NO MORE convincing recognition could be accorded Aerol Landing Struts than their adoption as standard equipment by such manufacturers as these. It gives the oleo-pneumatic principle of absorbing landing shock definite supremacy.

The fact that 23 manufacturers have standardized (and that practically all others offer Aerol Struts as optional equipment) makes it possible for the entire operating end of the aircraft industry to enjoy a degree of landing comfort, safety and economy that is not afforded by any other type of landing gear.

Aerol Struts are manufactured at Cleveland by the Cleveland Pneumatic Tool Company.

Ask the Pilots Who Land On Them

AEROL shock absorbing **STRUT**

Some typical EDO Float Installations

All of these Ships have been licensed as EDO-Equipped Seaplanes



Ryan B-5
Weight 3.4 gross tons



Travel Air Explorer
Explorer seaplane



Bellanca CH
Weight 3.4 gross tons



Commodore Air
Warner seaplane



Fokker Universal
Weight 3.5 tons



Curtiss Robin
Challenger seaplane



Stearman C3-B
Weight 3.5 tons



Waco 10
Worked seaplane



Sukkerbald Vega
Wing seaplane



Mads
Wing seaplane



Travel Air Monoplane
Wing seaplane



Buhl CA-6
Weight 3.4 gross tons

Edo Standardized All-Metal Seaplane Floats are available in a complete series for all planes up to gross pounds, gross load.



For prices and particulars of Standardized Edo Float Installations, address Edo Aircraft Corp., Box and St., College Point, L. I., N. Y.

This is one of a series of advertisements directed originally to advertising men in an effort to make industrial advertising more profitable in larger and better. It is printed on these pages as an indication to readers that McGraw-Hill publishing standards mean advertising effectiveness as well as editorial quality.

Every day is moving day in industry



JUST suppose we sold you the McGraw-Hill list of 600,000 paid subscribers. We wouldn't—but just suppose we did. A year from today it would be a source of complaint to you unless you also had:

a...Our circulation staff of 100 field men who will travel nearly a million miles during 1929, checking, checking, checking.

b...The good will of thousands of subscribers who voluntarily inform us of their changing responsibilities and addresses month after month.

c...The Second Class postal privileges that automatically correct addresses when addressees do not.

What is a perfectly good industrial list today will be at least 25% defective a

year from today. For example: We have checked the 1928 records of 13 of the 26 McGraw-Hill publications which have a circulation of 210,176 paid subscribers.

Were it not for these channels of checking, this list of 210,176 names would have contained on December 31, 1928, deadwood to the extent of 48,120 names. Not on account of failure to renew nor delay in remitting, but because of changing functions and addresses brought about by:

<i>Plant expansion</i>	<i>Mergers</i>
<i>New projects</i>	<i>Advancement</i>
<i>Decentralization</i>	<i>Centralization</i>
<i>Out of business</i>	<i>Transfer</i>
<i>Out-and-out job changing</i>	
<i>Change of residence</i>	

McGraw-Hill PUBLICATIONS

New York	Chicago	Cleveland	Detroit	Philadelphia	St. Louis
Greenwich		San Francisco	Boston	London	



Gulfpriide Oil

**The Following Records
of Importance were made
while using GULFPRIIDE OIL
for Lubrication of Motors**

World's Endurance Record for Sustained Flight

July 11th to July 26th, 1925—F. O'Brien and B. Jackson with Curtiss-Robin plane "St. Louis Robin." Time in air 576 hours 21 minutes. Powered with Curtiss Challenger Motor using GULFPRIIDE OIL 120.

World's Altitude Record for Airplanes

May 21st, 1929—Lt. A. Sorenson, U. S. N., with Wright Apache plane, Anacostia, D. C. Altitude 39,140 feet. Powered with Pratt & Whitney Wasp motor using GULFPRIIDE OIL 120.

World's Altitude Record for Seaplanes

June 4th, 1925—Lt. A. Sorenson, U. S. N., with Wright Apache plane—Anacostia, D. C. Altitude 38,560 feet. Powered with Pratt & Whitney Wasp motor using GULFPRIIDE OIL 120.

Curtiss Marine Trophy Race (For Seaplanes and Flying Boats)

May 25th, 1928—Winton Lt. W. G. Tomlinson, U. S. N., with Curtiss Fighter—Anacostia, D. C. Average speed 160 miles per hour. Powered with Pratt & Whitney Wasp motor using GULFPRIIDE OIL 120.

GULFPRIIDE OILS are approved by leading Marine Engine Builders. Manufactured for Marine engine lubrication in five grades or body designations: Gulfpriide Oil 55, Gulfpriide Oil 100, Gulfpriide Oil 120, Gulfpriide Oil 150, Gulfpriide Oil 200.

Free sample trials and recommendations on request

GULF REFINING COMPANY
PITTSBURGH, PA., U. S. A.

60 million drops of Rain!



BEATING with increased love against wings and fuselages like no other home-coming demonstration, millions of rain drops pull the sparkling rain-drenched plane. You the driver tight control about the water as easily as a duck's back and the fabric is safeguarded from the moisture effects of the heavy rain—because the plane is Titanine-finished.

Titanine permeated drops furnish the highly stretched covering with a non-porous, glass-like surface that won't slip, crack, become flabby, or wear through in spots. The hazards of harmful weather ravages are reduced to a minimum where the airplane surface is Titanine-protected. The use of Titanine protects for years the commercial airplane manufacturer and the government's air service facilities in their proved durability.



**BOOKLETS
ON REQUEST**

Send for booklet "Titanine" drop and fuselage weathering, their protection and decorative finishes. Make this card up, fill in your name, address, and city, and mail to Titanine Division, Federal Aircraft Division, New York, New York.

»TITANINE»

MAINTAINS YOUR WING

STANDARD AIRPLANE FINISHES SINCE 1913

Write for
Booklet, Titanine, New York.

Complete—drop and fuselage finish information in
Titanine Division Booklet.

Name _____
Address _____
City _____ State _____

...A landing plane + a parked Lizzie = danger

OF course a flying field makes a fine place for sightseers to park their cars. But an airport is supposed to be devoted exclusively to flying. Pilots should not have to fight with Lizzies for room to land and take-off.

The airport operator can attract planes and reduce the risk of accident by giving pilots every foot of area the field affords.

Both sightseers and their cars can be effectively barred from the flying area of an airport with an Anchor Fence.

One of 75 Anchor offices is near you—Phone the local Anchor Fencing Specialist for advice about barrier protection or complete erection service.

ANCHOR POST FENCE COMPANY

Eastern Avenue and Kane Street, Baltimore, Md.
Albany, Boston, Chicago, Cleveland, Cincinnati, Denver, Detroit, Hartford, Kansas City, Memphis, Milwaukee, New York, Philadelphia, Pittsburgh, St. Louis, San Francisco, Seattle.

Representatives in other cities. For a list include district.

ANCHOR CHAIN LINK Fences



A NATION-WIDE FENCING SERVICE

The most Luxurious Plane



in America . .

decarated throughout in Schumacher Fabrics

Enthusiastic spectators found more than size, speed, and safety to marvel at in the new Boeing Army—largest and most luxurious flying boat in America.

Exclamations of wonder and admiration greeted a view of its beautiful interior—surprisingly roomy—decorated throughout according to the newest trends in interior decoration.

The modernistic scheme in basic tones of silver, tan, brown, and green is worked out entirely in Schumacher Fabrics. In his skillful use of textiles Frederick J. Pike, decorator of Bufile, has achieved results as modern and stimulating as the plane itself.

Our special department devoted to fabrics for airplane decoration offers an extensive variety of textiles that combine ornament, light weight, serviceability.

F. Schumacher & Co., Dept. T-10, 66 West 40th Street, New York, Importers, Manufacturers and Distributors to the world only. Offices also in Boston, Chicago, Philadelphia, Los Angeles, San Francisco, Grand Rapids, and Detroit.



Cooling, Quaker Rep. Schumacher, Decatur, Davenport, Dayton rep. See cushions, cushions, dress and suit hangings, covers, hangings, other fabrics. All of these fabrics combine light weight with exceptional serviceability.



Cooling, Quaker Rep. Schumacher, Decatur, Davenport, Dayton rep. See cushions, cushions, dress and suit hangings, covers, hangings, other fabrics. All of these fabrics combine light weight with exceptional serviceability.



Cooling, Quaker Rep. Schumacher, Decatur, Davenport, Dayton rep. See cushions, cushions, dress and suit hangings, covers, hangings, other fabrics. All of these fabrics combine light weight with exceptional serviceability.

F·SCHUMACHER·&CO

The airplane and its engine

- its construction
- its capabilities
- its governing principles

By C. B. CHAFFIELD
and C. F. TAYLOR

Authoritative Professor in the "Course in Development Engineering" at the Massachusetts Institute of Technology

HERE is a book for the reader who wishes to acquire a sound knowledge of the basic facts and theories of the airplane, and the airplane engine.

It is a sound, clear and simple discussion of the fundamental principles, construction and operation of the airplane and its engine. The book is first a treatise on the simple "principle" of the engine and the airplane; then, in the chapters on the engine and the airplane, the principles are applied to the construction and operation of the engine and the airplane.

Logic mathematics has been used, and a knowledge of only elementary physics and mathematics is required. Many of the data are graphically presented in the form of curves and there are diagrams and explained illustrations. There are 200 photographs and diagrams.

the book covers
such topics as:

- the life of a wing—developing the theory from Newton's laws of motion
- the causes for wing shapes
- the principles and the theory of air—motion
- the principles of lift or buoyancy in motion and airplane shapes designed to produce this buoyancy
- the theory and airplane control
- the regular laws, principles and requirements of the engine
- the construction of the modern airplane
- types of airplane, airplane laws, motion and construction

379 pages, 5 1/2 x 8
209 Illustrations, \$2.50

SEE YOUR COPY FOR 30 DAYS FREE

Money will be refunded the year after the delivery of the book. The book is not to be sold for less than \$1.00. The book is not to be sold for less than \$1.00. The book is not to be sold for less than \$1.00.

Mc Graw-Hill FREE EXAMINATION COUPON

McGraw-Hill Book Co., Inc., 325 Seventh Ave., New York
Send me a copy of "The Airplane and its Engine" (1929) for 30 days free examination. I will return it to you if I do not wish to purchase it. I will return it to you if I do not wish to purchase it.

Name _____
Address _____
City and State _____
Name of Airline _____
Subscription Rate: U. S. \$5.00 Canada \$5.00 Foreign \$6.00

Check one to be received by (Check only 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100)

Do you know that...

each month our subscription
department receives more
than 150 requests for "Back"
issues of AVIATION?

If we printed extra copies of
our weekly issues, we would
be glad to comply with these
requests, but unfortunately
we have no way of knowing
in advance just how many of
our new and old readers will
"miss" an issue.

But We Do Know—that each
of these requests indicates a
reader has "missed" just the
issue he could make valued
use of.

Insure your receiving
AVIATION regularly by
filling in the coupon
below, today

AVIATION

16th Ave. at 56th Street, N. Y. C.

Here is my check for \$4.00. Send me Aviation for 1 year (12 copies).

Name _____

Address _____

City and State _____

Name of Airline _____

Subscription Rate: U. S. \$5.00 Canada \$5.00 Foreign \$6.00

A VAN SCHAACK DISTRIBUTOR at your instant disposal...

is the ultimate aim of the Van Schaack Bros. Chemical Works, Inc., manufacturers of Aircraft Fasteners of unquestionable quality.

These firms already carry adequate stocks of Van Schaack products and are prepared to serve you at a moment's notice.

Anders Auto Supply Co.,
221 Milwaukee St.,
Milwaukee, Wis.

John E. Anderson, Sr. & Co.,
Meriden, Conn.

John Anderson Bros. Co.,
Chattanooga, Tenn.

Kelly-Hen-Thompson Co.,
200 E. 1st Ave. West,
Duluth, Minn.

McNally & Son,
318 N. Kansas St.,
Liberty, Kansas

Nelson Aircraft Supply Corp.,
100 2nd St.,
Milwaukee, Wis.

The United Aircraft of N.C. Inc., Winston, N. C.

DeLong Aircraft Co.,
435 Northampton Ave.,
Chicago, Ill.

Bishop's Garage & Service,
100 E. 1st St.,
St. Paul, Minn.

Stanton Equipment Co.,
San Antonio, Texas

Additional Distributors are desired in various Territories
Write for Descriptive Literature and Prices.

VAN SCHAACK BROS. CHEMICAL WORKS, Inc.


Manufacturers
of Aircraft
Fasteners

Pharmers, Dept. Engineers, Northampton, Massachusetts
Main Office and Plant, 1386 Avenue A, Chicago, Ill.
Telephone—Independence 8400

Write
for
Descriptive
Literature
and
Prices



HARTSHORN
THE RODS
AIRCRAFT
TIE RODS
STEWART HARTSHORN CO.
234 Fifth Avenue, New York City



Efficient stopping

Especially designed for airplanes is this Bendix 4-brake. It gives the most powerful braking force, yet it is simple, easy to install, dependable, perfectly unobstructed. It is based on the proven principles of the internationally known Bendix brakes for our automobiles.

Write and make sure you understand

the Bendix 4-brake system.

BENDIX BRAKE COMPANY
General Offices and Plant: South Bend, Ind.
Divisions at Boston, Anderson, Chicago, St. Louis, Chicago

BENDIX 4 BRAKES

FOR SAFETY



Airports and Aviation Buildings by Austin

COMPLETE Airport Service—preliminary surveys and reports, engineering surveys and plans, etc.

Design and Construction—grading, drainage, lighting, all necessary airport buildings and hangars, depots, etc. Also aircraft fueling buildings.

Ask for approximately 1934 and booklet "Airports and Aviation Buildings."

THE AUSTIN COMPANY
Airport Engineers and Builders

Cleveland, Ohio, Chicago, Pittsburgh, Cincinnati, St. Louis, Kansas City, St. Paul, Minneapolis, Portland, Maine, and the County of Franklin, Mass.



The Department of Commerce has approved the new Brownback C-400...

Featured by simplicity of construction, economy of operation and low c. p. m., this new aircraft engine is ideal for commercial flying.



BROWNBACK
AIRCRAFT ENGINES
Graybar Building, New York

COLONIAL GRAIN UPHOLSTERY LEATHER

made by

EAGLE-OTTAWA LEATHER COMPANY
Grand Haven, Mich.

Genuine leather for airplanes in **NON-INFLAMMABLE** durable and clean.

Sample books furnished on application.

Chicago, Ill.
111 W. Washington St.
St. Louis, Mo.
1010 Locust St.
1215-1217-1218

St. Paul, Minn.
100 W. Wabash St.
St. Paul, Minn.
100 W. Wabash St.

FAIRCHILD

closed monoplane and open biplanes form a complete line of quality aircraft for dealers' sales. Fairchild aviation products also include propellers, skis, landing lights and engines. Dealers receive Fairchild Airplane Manufacturing Corporation, Farmington, I. T. E. S. A.



AIRPLANES



THE AIRBOSS SCORES AGAIN!



TWO stately stock model Air Boss biplanes, competing in the Miami-to-Cleveland Air Derby, won third place in Class C and sixth place in Class B. This remarkable showing was made with passengers, pay loads, open cockpits and double winchairs. These were the only two planes in the Derby racing under such handicaps. It is also interesting to note many planes of greater power were competing in each class.

The Air Boss further demonstrated its superior qualities by placing first three times and second once in the four Dead Stick Landings Events entered. Its remarkable control features made it an easy winner in this important field of competition.

"One first prize was disqualified on account of motor, with switch off, kicking over during glide to landing."

**SOUTHERN
AIRCRAFT
CORPORATION**

BIRMINGHAM, ALABAMA

FLY A CAVALIER



STAND
HER ON
THE PROP
AND

establish a gauge by which you can measure the performance and stability of other good airplanes... The nearest dealer will gladly afford you this opportunity.

Star Aircraft Co.
BARTLESVILLE, OKLAHOMA



IN THE AIR

Don't be satisfied with a lesser quality than "the best motor oil in the world."

THE PENNZOIL COMPANY, Oil City, Pa.

PENNZOIL

HIGHEST QUALITY 100% SUPREME
PENNSYLVANIA OIL



Cheney-Cast Cylinders widen your market

In these days when sales are so critical, the number of leads in reaching them and more important to secure them.

An investigation of the possibilities in Cheney-Cast cylinders is capital to gain definite new markets and, also, to reach the largest cylinder user in your community.

S. Cheney and Son
Madison, N. Y.

Who are They?

William H. Miller, Chief of Research, Hinged in an outstanding expert in development, designed the first models of M. & V. and was in charge of the research laboratory. Staff: J. Owens, Chief of Production, formerly in research; Ben Carter, in charge of the first production models. Export given through H. J. Johnson.

**BERLINER-JOYE
AIRCRAFT CORPORATION**
BALTIMORE MARYLAND



William H. Miller
Chief of Research



J. Owens
Chief of Production

Cunningham-Hall Airplanes

All-metal structure — insures durability, lower maintenance and greater safety.

Manufactured by
**CUNNINGHAM-HALL
AIRCRAFT CORPORATION**
33 Canal St.
ROCHESTER, NEW YORK

PROTECTION
CONSOLIDATED INSTRUMENTS
CONSOLIDATED INSTRUMENTS CO., INC.
100 East 42nd Street, New York City

KITTY HAWK
Five Like a Hawk—Land Like a Kite
The Ideal Ship
For Training Schools
BIRMINGHAM AIRCRAFT CORP.
BIRMINGHAM, N. Y.

OK
THE AIRCRAFT CORPORATION
100 East 42nd Street, New York City

PITCAIRN AIRCRAFT
For Air Mail use . . . SUPER MAILING
For Sport or Private use . . . SPORT MAILING
PITCAIRN AIRCRAFT, Inc.
New York City

"Opportunity" Advertising:
Think "SEARCHLIGHT" First!

UNIVERSAL AVIATION CORPORATION
LANSFORD, ST. LOUIS AIRPORT, ANGELO, MISSOURI

Aluminum Fuel and Oil Tanks

"Tank up with the leaders"

Lightest aluminum welded tank per gallon — most durable — highest safety factor. Prices in range with commercial aviation.

See our exhibit at the Cleveland Show, Booth 227

Streloff-Naughton CORPORATION
55 Williams Street, Long Island City, N. Y.
Telephone: ELston 5-1040

Heat Treated Forgings

Greatest strength with least weight

We are pioneers in the production of highest grade stretch and maximum forgings, and we now have one of the most up-to-date heat-treating plants in the country.

Consult us on your requirements. We will gladly place our equipment and resources at your disposal.

The Endicott Forging & Mfg. Co., Inc.
50 North Street, Endicott, N. Y.

ENDICOTT
"The forging people who satisfy"

Only reliable products
can be continuously
advertised

Radio in Aviation

for all Aeronautical Requirements!

The most complete line of Radio Equipment ever available to aviation. The most complete line of Radio Equipment ever available to aviation. The most complete line of Radio Equipment ever available to aviation.

DURHAM METALLIZED
RESISTORS AND POWERHOOMS
EXTRAORDINARY RESISTANCE TO OXIDATION AND CORROSION

SEAMLESS STEEL TUBING

All Aircraft Grades

WATERMAN STEEL CO. INC.
100 East 42nd Street, New York City

SERVICE STEEL COMPANY
100 East 42nd Street, New York City

BENT-WOOD WING ENDS
(UNLAMINATED)

Wings for the Best Growth of AVIATION QUALITY

We bend wing ends and other curved parts of solid wood, with strength, durability, and consistent results. Our leading experience of 30 years is at your service.

H. G. SHEPARD & SONS
One Street, Conn.

ALPHABETICAL INDEX TO ADVERTISEMENTS

[illegible]

Benjamin L. Givens
Vice President

[illegible]

August Savings Certificate

[illegible]

Professional Services

[illegible]

When to Fly

[illegible]

Great Lakes Scores Again!

DURING the National Air Races at Cleveland, Great Lakes proved again—and most convincingly—that a sturdy, rugged, lightweight ship, designed and built for training may also possess the speed and extreme maneuverability of a sport pursuit job.

Here are the results, in races open to planes powered with motors of 510 cubic inches. And remember—Great Lakes' American Cirrus Motor has a displacement of only 310 cubic inches.

Miami to Cleveland Derby—Sterilized Great Lakes Sport Trainer with Charlie Meyers at the controls, finished second. Great Lakes Sport Trainer, sturdy stock model, flown by Bert Hamill with baggage, tools and a mechanic finished fifth.

Women's Sixty Mile Closed Course Race — Straddy took Great Lakes Sport Tourers, piloted by Lady Mary Heath and Bleache Wilcox Noyes, finished second and third.

Men's Sixty Mile Closed Course Race—Streamlined Great Lakes Sport Trains, driven by Claude Meyers, took fourth place against a large field.

A thorough knowledge of aviation engineering, with a consequent perfection of design, plus practical experience in standardized production of aircraft in a large, well organized and modern plant, has made the Great Lakes Sport Trainer dominant among light planes.

Just the kind of ship you have always hoped someone would build—ideal for training, for business or for sport living. A new booklet describes it in detail. Send for it.

GREAT LAKES  AIRCRAFT
CORPORATION CLEVELAND



Manufactured under U. S. Department of Commerce Approved Type Certificate Number 278

THE WHIRLWIND J-6 AND ITS DEBUT AT CLEVELAND



THE Cleveland show brought thousands of men nearer to a seat in an airplane . . . it brought thousands of hands a little closer to their place upon the stick.

For the new planes, the new engines, and the new records earned their headlines and their cheers. The new progress of aviation seeped by radio, by eyesight, by printing press and voice to all quarters of the land.

Brilliant among the performances were those of the new Wright J-6's. Their power, their speed, their ease of handling announced to all who flew them that another great step has been made in the development of air-cooled engines, and the new J-6 engines have surpassed the famous old J-5, with which honored hero so many famous names have been inseparable!

Look to Wright, then, for more records and more performance! For the J-6 series gives plane designers new horizons to march on—and pilots more power back of the gun!

The motor is still the heart of the airplane. And the accomplishments of the J-6 series . . . even more than daring deeds and new records . . . bring nearer the day when men will take their ways upon the air in calmness, speed, and surety!



WRIGHT
AERONAUTICAL CORPORATION
PATERSON, NEW JERSEY

